

Enclosures and tanks 250-1000 kW gensets



> Specification sheet

Our energy working for you.™



**Power
Generation**

Enclosure standard features

- 14-gauge steel construction (panels)
- Stainless steel hardware
- Zinc phosphate pretreatment, e-coat primer and super durable powder topcoat paint minimize corrosion and color fade
- Package listed to UL 2200
- Designed to satisfy National Electrical Code installation requirements
- Fuel and electrical stub-up area within enclosure perimeter
- Fixed louvers
- Cambered roof prevents water accumulation
- Recessed, lockable doors in two sides
- Retainers hold doors open for easy access
- Enclosed exhaust silencer ensures safety and protects against rust
- Rain cap
- Exterior oil and coolant drains with interior valves for ease of service
- Rodent barriers on inlet
- Non-hygroscopic sound attenuating material
- Side mounted controls and circuit breakers
- Easy access lifting points for spreader bars
- Dual vibration isolation system (250-500 kW)
- Spring vibration isolation system (600-1000 kW)
- Enclosure mounts to lifting base or fuel tank (250-500 kW)
- Enclosure mounts to lifting base (600-1000 kW)
- Factory pre-assembled package
- Designed for outdoor use only
- Externally mounted emergency stop button for operator safety (optional on 250-500 kW)
- Horizontal air discharge to prevent leaf and snow accumulation (600-1000 kW)

Options

- Three levels of sound attenuation
- Motorized louvers to protect from ice and snow accumulation (available on air inlet for all models and on air outlet on level II, 250-500 kW enclosures only)
- Horizontal air discharge, sound level 2 only (250-500 kW)
- Aluminum construction with roll-coated polymer paint
- Wind rated to 150 mph (aluminum enclosures)
- Neutral sandstone paint color (aluminum only)
- Factory mounted battery charger
- External 120 VAC service outlet
- Rain hoods for air inlet (250-500 kW)
- Lifting base in lieu of a sub-base tank (250-500 kW)
 - Pre-wired AC distribution package
 - 100 amp (250-500 kW) or 150 amp (600-1000 kW) main circuit breaker; connected to 120 VAC line-neutral and 208 or 240 VAC line-line, spare breaker positions and capacity for future upgrades (600-1000 kW)
 - GFCI protected internal 120 VAC service receptacle
 - GFCI protected weather proof external 120 volt service receptacle
 - All factory installed AC powered features pre-wired into load center
- Interior lights – 120 volt (600-1000 kW)
- Rain hoods for air inlet (250-500 kW)
- Seismic isolators available (600-1000 kW)

Fuel tanks

Standard sub-base tank features

- UL 142 Listed
- ULC-S601-07 Listed
- NFPA37 compliant
- Dual walled, steel construction
- Emergency tank and rupture basin vents
- Tank mounted mechanical fuel gauge
- Fuel supply and return tubes
- Top mounted leak detection float switch
- Low and high level fuel switches
- Mounting brackets for optional pump and control (250-500 kW)
- Integral lifting points
- Basin drain

Sub-base tank options

- Pre-wired fuel pump and control
- Fuel overfill alarm – internal or external
- Overflow and tank fill plugs
- Five gallon spill fill box – internal or external
- Fill pipe extender
- Local code approvals available

200-500 kW dual wall sub-base fuel tanks – usable operating hours

Genset model (60 Hz)	Gallons/hour at full load	270 gallon tank	300 gallon tank	400 gallon tank	500 gallon tank	600 gallon tank	660 gallon tank	720 gallon tank	850 gallon tank	1470 gallon tank	1700 gallon tank	2100 gallon tank	2525 gallon tank
250 DQDAA	20	13	16	20	24	30	32	37		74			
275 DQDAB	21	12	15	18	22	27	30	34		68			
275 DQHAA	22	12	14	18	21	27	29		39		81		
300 DQDAC	23	11	14	17	20	25	27	31		63			
300 DQHAB	23	11	14	17	20	25	27		36		76		
350 DFEF	24	11	13	16	19	24	26		35		73		104
400 DFEH	27	10	12	14	17	21	23		31		64		92
450 DFEJ	30	9	10	13	15	19	21		28		58		83
500 DFEK	34	8	9	11	14	17	18		25		51		73

Operating hours are measured at 60 Hz, standby rating.

600-1000 kW dual wall sub-base fuel tanks – usable operating hours

Genset model	Gallons/hour at full load	200 gallon tank	660 gallon tank	1000 gallon tank	1500 gallon tank	2000 gallon tank	2400 gallon tank	3000* gallon tank
600 DQCA	42	4	14	23	35	47	57	72
600 DQPAA	45	4	15	22	33	44	53	67
600 DQPAB	50	4	13	20	30	40	48	60
750 DQCB	51	4	12	19	29	39	47	58
750 DQFAA	53	3	11	19	28	37	46	57
800 DQCC	53	3	11	18	28	37	45	57
800 DQFAB	56	3	11	17	26	35	43	53
900 DQFAC	64	3	9	15	23	31	38	47
1000 DQFAD	72	3	8	14	21	27	33	42

*3000 gallon tank offered as an accessory kit

- Operating hours are measured at 60Hz, standby rating.
- Up to 90% fill alarm to comply with NFPA30, operating capacity is reduced by 10%.

Our energy working for you.™

www.cumminspower.com

©2013 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. PowerCommand and "Our energy working for you." are trademarks of Cummins Power Generation. Specifications are subject to change without notice.
S-1443y (5/13)



Enclosure package sound pressure levels @ 7 meters dB(A)

Genset model	Weather protective enclosure (F200, F203)	QuietSite Level 1 sound attenuated enclosure (F201, F204)	QuietSite Level 2 sound attenuated enclosure (F202, F205)
250 DQDAA	90	88	72
275 DQDAB	90	88	73
275 DQHAA	86	85	74
300 DFCB	86	84	71
300 DQDAC	90	88	73
300 DQHAB	89	88	76
350 DFCC	87	85	72
350 DFEG	86	85	72
400 DFCE	89	85	73
400 DFEH	87	85	73
450 DFEC	89	85	75
450 DFEJ	88	85	74
500 DFED	90	86	76
500 DFEK	89	87	73
600 DFGB	85	78	74
600 DQCA	86	78	74
600 DQPAA	89	80.7	77.19
600 DQPAB	90	81.36	80.27
750 DFGE	87	80	75
750 DFHA	91	81	77
750 DQCB	87	79	74
750 DQFAA	89	79	75
800 DFHB	91	81	77
800 DQCC	87	79	74
800 DQFAB	89	79	75
900 DFHC	93	83	78
900 DQFAC	89	80	76
1000 DFHD	90	80	76
1000 DQFAD	90	80	76

- All data is 60Hz, full load standby rating, steel enclosures only.
- Data is a measured average of 8 positions.
- Sound levels for aluminum enclosures are approximately 2 dB(A) higher than listed sound levels for steel enclosures.



**250-1000 kW
Weather protective**



**250-1000 kW
QuietSite Level 2**

Our energy working for you.™

www.cumminspower.com

©2013 Cummins Power Generation Inc. All rights reserved. Cummins Power Generation and Cummins are registered trademarks of Cummins Inc. PowerCommand and "Our energy working for you." are trademarks of Cummins Power Generation. Specifications are subject to change without notice.
S-1443y (5/13)



Package dimensions of enclosure, exhaust system, and UL tank

250-500 kW

Tank size (gal)	Weather protective package length (in)	QuietSite level 1 package length (in)	QuietSite level 2 package length (in)	Width (in)	Height (in)	Weather protective package weight (lbs)	QuietSite level 1 package weight (lbs)	QuietSite level 2 package weight (lbs)
300	188	188	222	82	104	5648	6073	6991
400	188	188	222	82	106	5833	6258	7176
500	188	188	222	82	108	5956	6381	7299
600	188	188	222	82	111	6116	6541	7459
660	188	188	222	82	113	6235	6660	7578
720	188	188	222	82	114	6174	6599	7517
850	188	188	222	82	118	6529	6954	7872
1470	200	200	200	82	128	7428	7853	8771
1700	234	234	234	82	128	7982	8407	9325
Lifting base	188	188	222	82	100	4335	4760	5678

600-1000 kW

Tank size (gal)	Weather Protective package length (in)	QuietSite level 1 package length (in)	QuietSite level 2 package length (in)	Width (in)	Height (in)	Weather protective package weight (lbs)	QuietSite level 1 package weight (lbs)	QuietSite level 2 package weight (lbs)
200	260	303	315	98	129	10194	13074	14954
660	260	303	315	98	131	9586	12466	14346
1000	260	303	315	98	143	10117	12997	14877
1500	260	303	315	98	145	10677	13557	15437
2000	292	327	327	98	143	11959	14839	16719
2400	338	338	338	98	143	12961	15841	17721

- This weight does not include the generator set. Consult your local Cummins Power Generation distributor or the appropriate generator specification sheet.
- Width is 86" lifting eye to lifting eye (250-500 kW), 102" lifting eye to lifting eye (600-1000 kW).
- Height - Florida, Michigan, and Suffolk add 4" (250-500 kW) or 2" (600-1000 kW) for bottom space.
- Maximum length emergency vent removed.



CSA - The generator set is CSA certified to product class 4215-01.



UL - The generator set is available Listed to UL 2200, Stationary Engine Generator Assemblies. The PowerCommand control is Listed to UL 508 - Category NITW7 for U.S. and Canadian usage.

See your distributor for more information

Americas

1400 73rd Avenue N.E.
Minneapolis, MN 55432 USA
Phone: 763 574-5000
Fax: 763 574-5298