



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
 SHAWNEE MISSION, KANSAS 66227-2705
 DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
 (800) 322-9710 (800) 524-6474



www.pennysconcrete.com
 An Equal Opportunity Employer



American Concrete Institute®
 Certifications



Certifications

KANSAS
 DEPARTMENT OF TRANSPORTATION
 Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	09/11/2013	BLISS	0174	Shawn Cool	1087592

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - STRAIGHT NORTH AT GATE
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS ***BLISS CR	



37,977

NOTE:
 ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
13	TEC# 000003471	ROCKCHALKPAR		EXTFW	118	1.5
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	690	690		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS:		yds gal	yds gal

SUB TOTAL
 TAX
 TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____
 CUSTOMER SIGNATURE _____
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16561 lb	16620 lb	0.36%	2.10% M	41	gf	
SANDFAA	1327 lb	13566 lb	13600 lb	0.25%	2.23% A	36	gf	
CEMENT	450 lb	4500 lb	4515 lb	0.33%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	11.50 oz #	115.00 oz	115.00 oz	0.00%				
WATER	30.2 gl	205.7 gl	205.0 gl	-0.34%		205.0	gl	-2.00 gl

Num Batches: 1
 Design W/C: 0.420 Water/Cement: 0.419 T
 Design 302.0 gl Actual 281.5 gl Manual 13:16:54
 Adjust Water: 0.0 gl / Load Trim Water -2.0 gl / To Add: 20.5 gl
 Water in Truck: 0.0 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	09/12/2013	BLISS	0171	GREG MOHR	1087693

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - STRAIGHT NORTH AT GATE
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS ***BLISS CR	



37,909

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
14	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	114	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	930	930		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds ___ gal ___ yds ___ gal ___ yds ___ gal ___ yds ___ gal ___

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

X _____
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16350 lb	16350 lb	0.00%	0.80% M	16	gl	
SANDFAA	1327 lb	13589 lb	13640 lb	0.37%	2.41% A	38	gl	
CEMENT	450 lb	4500 lb	4500 lb	0.00%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	9.50 oz #	95.00 oz	95.00 oz	0.00%				
WATER	30.2 gl	228.2 gl	227.0 gl	-0.52%		227.0	gl	-2.00 gl

Num Batches: 1
Manual 16:55:49
Design 302.0 gl Actual 280.9 gl To Add: 21.1 gl
Design W/C: 0.420 Water/Cement: 0.420 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT
Water in Truck: 0.0 gl



PENNY'S CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	09/23/2013	BLISS	0146	GLYNN TIPTON	1088108

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAM WAY NORTH
JOB ADDRESS	THROUGH GATE FOLLOW DIRTROAD ON LEFT TAKE
6100 ROCK CHALK DR - ROCK CHALK	HAUL RD NORTHTO 3RD ENTRANCE EAST INTO
PARK - LAWRENCE, KS	PAVING



37,929

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
19	TEC# 000003471	ROCKCHALKPAR		MAINLINE	129	1.5
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	820	820		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

_____ X _____
 PRINTED NAME TITLE CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	20.00 oz	200.00 oz	201.00 oz	0.50%				
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
ROCKGMKC	1622 lb	16512 lb	16540 lb	0.17%	1.80% M	35	gl	
SANDFAA	1327 lb	13695 lb	13720 lb	0.19%	3.20% M	51	gl	
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WATER	30.2 gl	196.1 gl	195.0 gl	-0.58%		195.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				

Num Batches: 1
 Manual 14:44:45
 Design 302.0 gl Actual 281.0 gl To Add: 21.0 gl
 Water/Cement: 0.419 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC
 # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	09/24/2013	BLISS	0146	GLYNN TIPTON	1088234

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAM WAY NORTH -
JOB ADDRESS	STRAIGHT NORTH AT GATE
6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS ***BLISS CR	

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
5	TEC# 000003471 8	ROCKCHALKPAR			123	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	770	750		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL TAX TOTAL
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal				

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	19.00 oz #	190.00 oz	190.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4500 lb	0.00%				
ROCKGMKC	1622 lb	16398 lb	16420 lb	0.13%	1.10% M	21	gl	
SANDFAA	1327 lb	13714 lb	13710 lb	-0.03%	3.35% A	53	gl	
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WATER	30.2 gl	207.4 gl	206.0 gl	-0.66%		206.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				

Num Batches: 1

Manual 15:47:19

Design 302.0 gl Actual 280.6 gl To Add: 21.4 gl

Design W/C: 0.420 Water/Cement: 0.419 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYE

37890 lb # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	09/25/2013	BLISS	0161	TRAVIS WORRELL	1088276
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS ***BLISS CR			6TH ST. WEST - GEORGE WILLIAM WAY NORTH - THROUGH GATE FOLLOW DIRT ROAD ON LEFT TO TRACK HEAD WEST AROUND TRACK AND AROUND TO THENORTH ALL THE WAY TO PAVING		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK
85	TEC# 000003471	ROCKCHALKPAR		MAINLINE	114
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED
10.00	yd	AS6425G4	KCMMB 4K .42 25%	260	240
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0	

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

PRINTED NAME	TITLE	CUSTOMER SIGNATURE
		X
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT		

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16415 lb	16430 lb	0.09%	1.20% M	23	gl	
SANDFAA	1327 lb	13696 lb	13730 lb	0.25%	3.21% A	51	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	301.00 oz	0.33%				
AIR1	18.00 oz #	180.00 oz	179.00 oz	-0.56%				
WATER	30.2 gl	207.6 gl	207.0 gl	-0.29%		207.0	gl	-2.00 gl

Num Batches: 1
 Design W/C: 0.420 Water/Cement: 0.420 T Design 302.0 gl Actual 281.6 gl To Add: 20.4 gl
 Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC
 Manual 11:51:07



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 09/26/2013	ACCOUNT BLISS	TRUCK 0123	DRIVER NAME TIMOTHY BELTON	TICKET # 1088418		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - THROUGH GATE - NORTH ON HAUL ROAD - BACK DOWN TO PAVER				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS ***BLISS CR			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
37,944							
ORDER # 4	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION	PREVIOUS TRUCK 123 SLUMP 1.5		
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	606	606		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	18.00 oz	180.00 oz	180.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4520 lb	0.44%				
ROCKGMKC	1622 lb	16496 lb	16550 lb	0.33%	1.70% M	33	gl	
SANDFAA	1327 lb	13642 lb	13650 lb	0.06%	2.80% A	45	gl	
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WATER	30.2 gl	204.4 gl	203.0 gl	-0.68%		203.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				

Num Batches: 1 Manual 15:42:22

Design 302.0 gl Actual 280.7 gl To Add: 21.3 gl

Design W/C: 0.420 Water/Cement: 0.419 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT

Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	09/30/2013	BLISS	0139	Kevin Tolbert	1088650

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAM WAY NORTH -
JOB ADDRESS	THROUGH GATE - NORTH ON HAUL ROAD - BACK
6100 ROCK CHALK DR - ROCK CHALK	DOWN TO PAVER
PARK - LAWRENCE, KS ***BLISS CR	



37,926

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
14	TEC#	ROCKCHALKPAR			159	4
	000003471					
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	820	820		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C84 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16415 lb	16450 lb	0.22%	1.20% M	23	gl	
SANDFAA	1327 lb	13602 lb	13610 lb	0.06%	2.50% M	40	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WREDUCE1	30.00 oz	300.00 oz	301.00 oz	0.33%				
AIR1	7.00 oz #	70.00 oz	70.00 oz	0.00%				
WATER	30.2 gl	218.9 gl	219.0 gl	0.04%		219.0	gl	-2.00 gl

Num Batches: 1
Manual 19:00:51
Design 302.0 gl Actual 282.2 gl To Add: 19.8 gl
37926 lb Design W/C: 0.420 Water/Cement: 0.419 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC
4.00 in # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	10/01/2013	BLISS	0114	BRIAN LINDELOF	1088747

CUSTOMER NAME
BLISS SPORTS LLC

JOB ADDRESS
6100 ROCK CHALK DR - ROCK CHALK
PARK - LAWRENCE, KS ***BLISS CR

ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
6TH ST. WEST - GEORGE WILLIAM WAY NORTH -
THROUGH GATE - NORTH ON HAUL ROAD - BACK
DOWN TO PAVER



37,976

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
30	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	138	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	750	750		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME TITLE

X

CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16431 lb	16450 lb	0.12%	1.30% M	25	gl	
SANDFAA	1327 lb	13602 lb	13610 lb	0.06%	2.50% M	40	gl	
CEMENT	450 lb	4500 lb	4570 lb	+ 1.56%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	18.00 oz #	180.00 oz	180.00 oz	0.00%				
WATER	30.2 gl	217.0 gl	217.0 gl	0.01%		217.0	gl	-2.00 gl

Num Batches: 1 Manual 18.21:42
 Design 302.0 gl Actual 282.1 gl To Add: 19.9 gl
 Design W/C: 0.420 Water/Cement 0.415 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT
 Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 10/02/2013	ACCOUNT BLISS	TRUCK 0145	DRIVER NAME Steve Wilson	TICKET # 1088911
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - THROUGH GATE - NORTH ON HAUL ROAD - BACK DOWN TO PAVER		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS ***BLISS CR					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER # 12	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION	PREVIOUS TRUCK 139	SLUMP 2	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	1300	1240		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138; Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	10.00 oz	100.00 oz	99.00 oz	-1.00%				
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
ROCKGMKC	1630 lb	16479 lb	16510 lb	0.19%	1.10% M	22	gl	
SANDFAA	1332 lb	13653 lb	13670 lb	0.12%	2.50% M	40	gl	
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WATER	30.9 gl	212.6 gl	213.0 gl	0.18%		213.0	gl	-3.50 gl
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				

Manual 16:54:44
 Num Batches: 1
 Design 309.0 gl Actual 274.5 gl To Add: 34.5 gl
 Water/Cement: 0.429 T Adjust Water: 0.0 gl / Load Trim Water: -3.5 gl / CYT
 # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	10/04/2013	BLISS	0142	DERRICK MARLER	1089007

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAM WAY NORTH -
JOB ADDRESS	THROUGH GATE - NORTH ON HAUL ROAD - BACK
6100 ROCK CHALK DR - ROCK CHALK	DOWN TO PAVER
PARK - LAWRENCE, KS ***BLISS CR	



37,941

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
14	TEC#	ROCKCHALKPAR			151	1.5
000003471						
8						

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	320	320		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME

TITLE

X

CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16463 lb	16480 lb	0.10%	1.50% M	29	gl	
SANDFAA	1327 lb	13667 lb	13710 lb	0.32%	2.99% A	48	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	18.00 oz #	180.00 oz	179.00 oz	-0.56%				
WATER	30.2 gl	205.3 gl	205.0 gl	-0.16%		205.0	gl	-2.00 gl

Num Batches: 1
 Design 302.0 gl Actual 281.9 gl To Add: 20.1 gl
 Water/Cement: 0.419 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC
 37941 lb Design W/C: 0.420 Water in Truck: 0.0 gl
 1.50 in #

Manual 12:41:22



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute®
Certifications




Certifications

KANSAS

DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 10/09/2013	ACCOUNT BLISS	TRUCK 0094	DRIVER NAME Shawn Cool	TICKET # 1089115		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - STRAIGHT NORTH AT GATEAND FOLLOW ROAD AROUND TO PAVING AT NORTH END OF PROJECT				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
			38,098				
ORDER # 84	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION	PREVIOUS TRUCK 184 SLUMP 5		
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	200	160		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY _____

_____ X _____
PRINTED NAME TITLE CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16463 lb	16480 lb	0.10%	1.00% M	20	gl	
SANDFAA	1332 lb	13666 lb	13690 lb	0.17%	2.60% M	42	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	8.00 oz #	80.00 oz	79.00 oz	-1.25%				
WATER	30.9 gl	228.0 gl	227.0 gl	-0.42%		227.0	gl	-2.00 gl

Num Batches: 1
Design 309.0 gl Actual 288.1 gl To Add: 20.9 gl
Design W/C: 0.430 Water/Cement: 0.429 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYL
mp: 5.00 in # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET


SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute®
Certifications



Certifications


KANSAS

DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	10/09/2013	BLISS	0194	Mark Ice	1089124

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	

	26,619	NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!
---	--------	--

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
85	TEC# 000003471 8	ROCKCHALKPAR		MACHINE	110	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
7.00	yd	AS6425G4	KCMMB 4K .42 25%	77	77		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL TAX TOTAL
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal				

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	11490 lb	11550 lb	0.52%	1.20% M	16	gl	
SANDFAA	1327 lb	9574 lb	9570 lb	-0.04%	3.07% A	34	gl	
CEMENT	450 lb	3150 lb	3195 lb	+ 1.43%				
SLAG	150 lb	1050 lb	1065 lb	+ 1.43%				
WREDUCE1	30.00 oz	210.00 oz	210.00 oz	0.00%				
AIR1	18.00 oz #	126.00 oz	126.00 oz	0.00%				
WATER	30.2 gl	146.9 gl	146.0 gl	-0.62%		146.0	gl	-2.00 gl

Num Batches: 1 Manual 14:49:20

Design 211.4 gl Actual 196.6 gl To Add: 14.8 gl

Design W/C: 0.420 Water/Cement: 0.414 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC

Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	10/10/2013	BLISS	0194	Mark Ice	1089134

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAM WAY NORTH -
JOB ADDRESS	STRAIGHT NORTH AT GATEAND FOLLOW ROAD AROUND
6100 ROCK CHALK DR - ROCK CHALK	TO PAVING AT NORTH END OF PROJECT
PARK - LAWRENCE, KS	

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
40	TEC#	ROCKCHALKPAR		MAINLINE	110	5
	000003471					
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	160	30		
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal				
				SUBTOTAL
				TAX
				TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

_____ X _____
 PRINTED NAME TITLE CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16496 lb	16510 lb	0.09%	1.20% M	23	gl	
SANDFAA	1332 lb	13611 lb	13640 lb	0.22%	2.18% A	35	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	8.00 oz #	80.00 oz	80.00 oz	0.00%				
WATER	30.9 gl	230.7 gl	230.0 gl	-0.31%		230.0	gl	-2.00 gl

Num Batches: 1
 Manual 8:18.59
 ual 38108 lb Design W/C: 0.430 Water/Cement: 0.429 T Design 309.0 gl Actual 288.4 gl To Add: 20.6 gl
 rd 5.00 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 10/15/2013	ACCOUNT BLISS	TRUCK 0192	DRIVER NAME R L Henley	TICKET # 1089343
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - WEST THROUGH GATE AND FOLLOW HAUL ROAD NORTH		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

37,883

ORDER # 3	PO# TEC#	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION MAINLINE	PREVIOUS TRUCK 157	SLUMP 1.5
000003471						
8						

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	900	900		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1920	ARRIVE JOB 1930	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16528 lb	16530 lb	0.01%	1.90% M	37	gl	
SANDFAA	1327 lb	13662 lb	13670 lb	0.06%	2.95% A	47	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	301.00 oz	0.33%				
AIR1	17.00 oz	170.00 oz	170.00 oz	0.00%				
WATER	30.2 gl	198.1 gl	197.0 gl	-0.57%		197.0	gl	-2.00 gl

Num Batches: 1

Manual 19:10:41

Design 302.0 gl Actual 280.9 gl To Add: 21.1 gl

Design W/C: 0.420 Water/Cement: 0.419 T

mp: 1.50 in # Water in Truck: 0.0 gl just Water: 0.0 gl / Load Trim Water: -2.0 / CYL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	10/25/2013	BLISS	0157	JOHN BOLEY	1090001
CUSTOMER NAME			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
BLISS SPORTS LLC			6TH ST. WEST - GEORGE WILLIAM WAY NORTH -		
JOB ADDRESS			HAND PAVING IN SE PARKING LOT		
6100 ROCK CHALK DR - ROCK CHALK					
PARK - LAWRENCE, KS					
			NOTE:		
38,167			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,		
			STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
85	TEC# 000003471 8	ROCKCHALKPAR		HANDPAV	195	5	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	100	80		
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL	
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO		TAX
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal					TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

_____ X _____
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16561 lb	16590 lb	0.18%	1.60% M	31	gl	
SANDFAA	1332 lb	13842 lb	13910 lb	0.49%	3.92% A	63	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1520 lb	+ 1.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	6.50 oz #	65.00 oz	65.00 oz	0.00%				
WATER	30.9 gl	195.2 gl	194.0 gl	-0.61%		194.0	gl	-2.00 gl

Num Batches: 1

Manual 14:47:25

Design 309.0 gi Actual 288.2 gi To Add: 20.8 gi

Design W/C: 0.430 Water/Cement 0.428 T Design 309.0 gi Actual 288.2 gi To Add: 20.8 gi

mp: 5.00 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gi / Load Trm Water: -2.0 gl / CY

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66048
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 15:14	DATE 11/07/13	ACCOUNT BLISS04 722020	TRUCK 0095	DRIVER RON HELGET	TICKET 2038522
CUSTOMER NAME BLISS SPORTS			DELIVERY ADDRESS 6TH & G- WILLIAMS WAY THEN N ROCK CHALK PARK			
PURCHASE ORDER 6TH & GEO		SALES ORDER	TAX 68	CREDIT 2	SLUMP 2.00 in	

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
7.00	156421	KCMME 4K	34.00	34.00		

~~56.00~~ 1900 Unloading Charge

LOADED 14:46	ARRIVE JOB SITE 3:24	START DISCHARGE 3:36	FINISH DISCHARGE 4:50	ARRIVE PLANT 6:20
-----------------	-------------------------	-------------------------	--------------------------	----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.

ADDITIONAL WATER ADDED ON JOB	→	Gallons 32	By
-------------------------------	---	---------------	----

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eye, rinse immediately and repeatedly with water and get prompt medical attention. KEEP OUT OF REACH OF CHILDREN

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP
EXTRA CHARGE FOR OVER 30 MINUTES →

RECEIVED IN GOOD CONDITION
BY X

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line. If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0095	185	user	2038522	93951	14:46	11/7/13	
Load Size	Mix Code	Returned	Qty	Mix Age	Seq W	Load ID	
7.00	CYDS 156421					95963	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.78 GL	124.77 GL	124.00 GL	-0.61%		124.00 gl	
ADVA140	16.50 OZ	115.50 OZ	116.00 OZ	0.43%			
PVCA-5	1620 LB	11510 LB	11540 LB	0.26%	1.50% M	20 gl	
JPSAND	1325 LB	9565 LB	9540 LB	-0.26%	3.13% A	35 gl	
CENTRAL	450.0 LB	3150.0 LB	3150.0 LB	0.00%			
LAFGGBFS	150.0 LB	1050.0 LB	1045.0 LB	-0.48%			
DARA1400	5.00 OZ	35.00 OZ	35.00 OZ	0.00%			
Actual	Num Batches: 1						
Load Total:	26319 lb	Design 0.441	Water/Cement 0.441 T	Manual 14:46:32	Design 221.9 gl	Actual 179.1 gl	To Add: 42.8 gl
Slump: 2.00 in	# Water in Truck: 0.0 GL	Adjust Water: 0.0 GL	/ Load Trim Water: -4.0 GL/ CYD				

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 12:23	DATE 11/08/13	ACCOUNT ZZ2020 BL5204	TRUCK 0093	DRIVER WES SCHMITT	TICKET 2038580
CUSTOMER NAME BLISS SPORTS			DELIVERY ADDRESS 6TH & G- WILLIAMS WAY THEN N ROCK CHALK PARK			
PURCHASE ORDER 6TH & GEO	SALES ORDER	TAX 68	CREDIT 2			SLUMP 2.00 in
LOAD QTY. 7.00	PRODUCT 156421	DESCRIPTION KCMMB 4K	ORDERED 21.00	DELIVERED 21.00	UNIT PRICE	AMOUNT

LOADED 11:57	ARRIVE JOB SITE 12:29	START DISCHARGE 12:35	FINISH DISCHARGE 1:31	ARRIVE PLANT 2:22
-----------------	--------------------------	--------------------------	--------------------------	----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB →	Gallons 0	By
--	---------------------------------	--------------	----

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention.
KEEP OUT OF REACH OF CHILDREN

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP EXTRA CHARGE FOR OVER 30 MINUTES →
RECEIVED IN GOOD CONDITION BY X

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line. If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0093	232	user	2038580	94009	11:57	11/8/13	
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
7.00 CYDS	156421				W	96021	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.70 GL	129.52 GL	132.00 GL	1.91%		132.00 gl	
ADVA140	16.50 OZ	115.50 OZ	115.00 OZ	-0.43%			
PVCA-5	1620 LB	11510 LB	11520 LB	0.09%	1.50% M	20 gl	
JPSAND	1325 LB	9642 LB	9640 LB	-0.02%	3.96% A	44 gl	
CENTRAL	450.0 LB	3150.0 LB	3135.0 LB	-0.48%			
LAFGBFS	150.0 LB	1050.0 LB	1045.0 LB	-0.48%			
DARH100	5.00 OZ	35.00 OZ	35.00 OZ	0.00%			
Actual	Num Batches: 1				Manual 11:57:27		
Load Total:	26451 lb	Design 0.441	Water/Cement 0.443 T		Design 221.9 gl	Actual 196.4 gl	To Add: 25.5 gl
Slump:	2.00 in	# Water in Truck: 0.0 GL	Adjust Water: 0.0 GL / Load		Trim Water: -2.0 GL/ CYD		



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/11/2013	BLISS	0137	DAN LECKNER	1090492
CUSTOMER NAME			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
BLISS SPORTS LLC			6TH ST. WEST - PAST GEORGE WILLIAM WAY -		
JOB ADDRESS			NORTH ON GRAVEL ACCESSRD EAST OF ON RAMP FOR		
6100 ROCK CHALK DR - ROCK CHALK			10 HWY -EAST AT CONES		
PARK - LAWRENCE, KS					
			NOTE:		
18,996			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,		
			STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
3	TEC#	ROCKCHALKPAR		MAINLINE	160	1.5
000003471						
8						

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.00	yd	AS6425G4	KCMMB 4K .42 25%	715	715		
5.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

_____ X
 PRINTED NAME TITLE CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	14.00 oz	70.00 oz	70.00 oz	0.00%				
CEMENT	450 lb	2250 lb	2255 lb	0.22%				
ROCKGMKC	1622 lb	8215 lb	8270 lb	0.66%	1.30% M	13	gl	
SANDFAA	1327 lb	6903 lb	6930 lb	0.39%	4.04% A	32	gl	
SLAG	150 lb	750 lb	760 lb	1.33%				
WATER	30.2 gl	96.2 gl	92.0 gl	-4.39%		92.0	gl	-2.00 gl
WREDUCE1	30.00 oz	150.00 oz	150.00 oz	0.00%				

Num Batches: 1 Manual 14:26:10
 Design 151.0 gl Actual 137.0 gl To Add: 14.0 gl
 18996 lb Design W/C: 0.420 Water/Cement: 0.418 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT
 1.50 in # Water in Truck: 0.0 gl

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT	TIME	DATE	ACCOUNT	TRUCK	DRIVER	TICKET
21	12:20	11/11/13	772020 BL2204	0133	CALEB RICKETTS	21002125
CUSTOMER NAME			DELIVERY ADDRESS			
BLISS SPORTS			6TH & G- WILLIAMS WAY THEN N ROCK CHALK PARK			
PURCHASE ORDER		SALES ORDER	TAX	CREDIT	SLUMP	
6TH & GEO			68		2.00 in	
LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
6.50	156421	KCMMB 4K	40.00	31.50		

LOADED	ARRIVE JOB SITE	START DISCHARGE	FINISH DISCHARGE	ARRIVE PLANT
11:46	12:22	12:41	1:12	1:43

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB	Gallons	By
	→	6	

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eye, rinse immediately and repeatedly with water and get prompt medical attention.
KEEP OUT OF REACH OF CHILDREN

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP EXTRA CHARGE FOR OVER 30 MINUTES	→
RECEIVED IN GOOD CONDITION	
BY X	

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line.
If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0133	030	user	21002125	2196		11:46	11/11/13
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
6.50 CYDS	156421				D	2288	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.70 gl	126.82 gl	127.00 gl	0.14%		127.00 gl	
ADVA140	16.50 oz	107.25 oz	110.00 oz	2.56%			
PVCA-5	1620 lb	10535 lb	10600 lb	-0.33%	1.00% M	13 gl	
JPSAND	1325 lb	8951 lb	8900 lb	-0.57%	3.94% A	40 gl	
CENTRAL	450.0 lb	2925.0 lb	2900.0 lb	-0.85%			
LAFGBBFS	150.0 lb	975.0 lb	965.0 lb	-1.03%			
DARA1400	5.50 oz	35.75 oz	36.00 oz	0.70%			
WATER 2	.00 #	.00 gl	.00 gl				
Actual	Num Batches:						
Load Total:	24434 lb	Design 0.441	Water/Cement 0.445 T	Manual	11:46:07		
Slump:	2.00 in	# Water in Truck:	0.0 gl	Adjust Water:	0.0 gl	/ Load	Trim Water: -2.0 gl/ CYD
						Actual 180.0 gl	To Add: 26.1 gl

OFFICE ORIGINAL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 11/12/2013	ACCOUNT BLISS	TRUCK 0193	DRIVER NAME Robert Crosby	TICKET # 1090519
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST WEST - GEORGE WILLIAMS WAY NORTH - PAST PAVER ON NEW CONCRETE		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER # 23	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION MAINLINE	PREVIOUS TRUCK 192	SLUMP 1.5
---------------	-------------------------------	------------------------------	------	-------------------------	-----------------------	--------------

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	330	20		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 12:18	ARRIVE JOB 12:30	START UNLOAD 1:30	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL	
TAX	
TOTAL	

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	12.00 oz	120.00 oz	120.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
ROCKGMKC	1622 lb	16463 lb	16600 lb	0.83%	1.50% M	29	gl	
SANDFAA	1327 lb	13683 lb	13720 lb	0.27%	3.12% A	50	gl	
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WATER	30.2 gl	203.3 gl	204.0 gl	0.34%		204.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				

ua: Num Batches: 1 Manual 12:13:59

id 38069 lb Design W/C: 0.420 Water/Cement: 0.419 T Design 302.0 gl Actual 283.1 gl To Add: 18.9 gl

mp 1.50 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 11/13/2013	ACCOUNT BLISS	TRUCK 0195	DRIVER NAME Marty Trumble	TICKET # 1090575		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST WEST - PAST GEORGE WILLIAMS WAY - NORTH ON ACCESS RD EAST OF HWY 10-EAST ONTO JOBSITE AT CONES				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
			26,565				
ORDER # 41	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION	PREVIOUS TRUCK 186	SLUMP 1.5	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
7.00	yd	AS6425G4	KCMMB 4K .42 25%	347	347		
7.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY

_____ X _____
PRINTED NAME TITLE CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	12.00 oz	84.00 oz	84.00 oz	0.00%				
CEMENT	450 lb	3150 lb	3160 lb	0.32%				
ROCKGMKC	1622 lb	11524 lb	11550 lb	0.22%	1.50% M	20	gl	
SANDFAA	1327 lb	9605 lb	9630 lb	0.26%	3.40% M	38	gl	
SLAG	150 lb	1050 lb	1055 lb	0.48%				
WATER	30.2 gl	139.1 gl	138.0 gl	-0.82%		138.0	gl	-2.00 gl
WREDUCE1	30.00 oz	210.00 oz	210.00 oz	0.00%				

Num Batches: 1 Manual 17:08:09
 Design W/C: 0.420 Water/Cement: 0.419 T Design 211.4 gl Actual 196.4 gl To Add: 15.0 gl
 # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 17:02	DATE 11/14/13	ACCOUNT BL2204	TRUCK 0135	DRIVER STEVEN WELKER	TICKET 2038820
CUSTOMER NAME BLISS SPORTS, L.C.			DELIVERY ADDRESS E902 & N 6TH TO E902 (BYPASS FRONTAGE) & N TO GRAVEL ENTRANCE & E TO REC CENTER			
PURCHASE ORDER NOT GEO.	SALES ORDER	TAX 68	CREDIT 2			SLUMP 1.25 in
LOAD QTY. 10.00	PRODUCT 156421	DESCRIPTION KCMME 4K	ORDERED 130.00	DELIVERED 130.00	UNIT PRICE	AMOUNT

Winter Service

LOADED 16:20	ARRIVE JOB SITE 5:15	START DISCHARGE 5:30	FINISH DISCHARGE 6:12	ARRIVE PLANT 6:44
-----------------	-------------------------	-------------------------	--------------------------	----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB →	Gallons 5	By
--	---------------------------------	--------------	----

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. KEEP OUT OF REACH OF CHILDREN

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP
EXTRA CHARGE FOR OVER 30 MINUTES →

RECEIVED IN GOOD CONDITION
BY X

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line. If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0135	197	user	2038820	94246	16:28	11/14/13	
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
10.00 CYDS	156421				W	96261	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.70 GL	194.82 GL	195.00 GL	0.09%		195.00 gl	
ADVA140	16.50 OZ	165.00 OZ	165.00 OZ	0.00%			
PVCA-5	1620 LB	16362 LB	16300 LB	0.11%	1.00% M	19 gl	
JPSAND	1325 LB	13711 LB	13620 LB	-0.67%	3.40% A	55 gl	
CENTRAL	450.0 LB	4500.0 LB	4460.0 LB	-0.89%			
LAFGBBFS	150.0 LB	1500.0 LB	1490.0 LB	-0.67%			
DARA1400	5.00 OZ	50.00 OZ	50.00 OZ	0.00%			
Actual	Num Batches: 1						
Load Total:	37591 lb	Design 0.441	Water/Cement 0.445	T	Design 317.0 gl	Actual 269.3 gl	To Add: 47.7 gl
Slump:	1.25 in	# Water in Truck: 0.0 GL	Adjust Water: 0.0 GL	/ Load	Trim Water: -2.0 GL/	CYD	Note: Manual feed ok

OFFICE ORIGINAL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/15/2013	BLISS	0184	Wayne Grammer	1090735

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - PAST GEORGE WILLIAM WAY -
JOB ADDRESS	NORTH ON ACCESS RD JUST BEFORE 10 HWY RAMP -
6100 ROCK CHALK DR - ROCK CHALK	1ST RIGHT INTO JOB
PARK - LAWRENCE, KS	



38,088

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
32	TEC#	ROCKCHALKPAR		MAINLINE	195	1.5
	000003471					
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	530	530		
10.00	oz	DARASET	DARASET 1.0% NON-CHLOF	1	8640		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL

TAX

TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	13.00 oz	130.00 oz	130.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
ROCKGMKC	1622 lb	16463 lb	16540 lb	0.47%	1.50% M	29	gl	
SANDFAA	1327 lb	13721 lb	13760 lb	0.28%	3.40% M	54	gl	
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WATER	30.2 gl	198.8 gl	202.0 gl	+ 1.62%		202.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
DARASET	96.00 oz	960.00 oz	960.00 oz	0.00%				

Num Batches: 1
Design 302.0 gl Actual 285.5 gl To Add: 16.5 gl
38088 lb Design W/C: 0.420 Water/Cement: 0.419 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT
1.50 in # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/18/2013	BLISS	0174	Shawn Cool	1090820

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - PAST GEORGE WILLIAM WAY -
JOB ADDRESS	NORTH ON ACCESS RD JUST BEFORE 10 HWY RAMP
6100 ROCK CHALK DR - ROCK CHALK	(902 RD) - 1ST RIGHT INTO JOB
PARK - LAWRENCE, KS	

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
16	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	116	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	720	720		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	34560		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL TAX TOTAL
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal				

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	13.00 oz	130.00 oz	130.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4515 lb	0.33%				
ROCKGMKC	1622 lb	16447 lb	16450 lb	0.02%	1.40% M	27	gl	
SANDFAA	1327 lb	13721 lb	13730 lb	0.08%	3.40% M	54	gl	
SLAG	150 lb	1500 lb	1515 lb	1.00%				
WATER	30.2 gl	200.7 gl	200.0 gl	-0.36%		200.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
DARASET	48.00 oz	480.00 oz	496.00 oz	3.33%				

Num Batches: 1

Design W/C: 0.420 Water/Cement: 0.418 T Design 302.0 gl Actual 281.3 gl To Add: 20.7 gl

Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CY



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute®
Certifications



Certifications



www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/19/2013	BLISS	0174	Shawn Cool	1090856

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAMS WAY NORTH -
JOB ADDRESS	WEST ONTO JOBSITE - NORTH ON CONCRETE HAUL
6100 ROCK CHALK DR - ROCK CHALK	ROAD - TAKE FIRST RIGHT ON CONCRETE
PARK - LAWRENCE, KS	

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
134	TEC#	ROCKCHALKPAR		MAINLINE	195	5
000003471						
8						

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	60	20		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16512 lb	16550 lb	0.23%	1.30% M	25	gl	
SANDFAA	1332 lb	13773 lb	13800 lb	0.20%	3.40% M	54	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	6.50 oz #	65.00 oz	65.00 oz	0.00%				
WATER	30.9 gl	209.3 gl	208.0 gl	-0.64%		208.0	gl	-2.00 gl

Num Batches: 1 Manual 15.00.43

Design 309.0 gl Actual 287.8 gl To Add: 21.2 gl

Design W/C: 0.430 Water/Cement: 0.429 T 0.0 gl / Load Trim Water: -2.0 gl / CY

Water in Truck: 0.0 gl Adjust Water: 0.0 gl /



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute®
Certifications



Certifications

KANSAS
STATEMENT OF MERCHANTABILITY
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/19/2013	BLISS	0161	TRAVIS WORRELL	1090834

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - PAST GEORGE WILLIAM WAY - NORTH ON ACCESS RD JUST BEFORE 10 HWY RAMP (902 RD) - 1ST RIGHT INTO JOB
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	



38,011

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
28	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	152	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	140	20		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	960		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

GRAND TOTAL

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X _____
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	14.00 oz	140.00 oz	140.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4500 lb	0.00%				
ROCKGMKC	1622 lb	16431 lb	16450 lb	0.12%	1.30% M	25	gl	
SANDFAA	1327 lb	13721 lb	13800 lb	0.57%	3.40% M	54	gl	
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WATER	30.2 gl	202.7 gl	203.0 gl	0.16%		203.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
DARASET	48.00 oz	480.00 oz	464.00 oz	-3.33%				

Num Batches: 1

Design W/C: 0.420 Water/Cement: 0.419 T Design 302.0 gl Actual 282.7 gl To Add: 19.3 gl

Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CY

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 10:42	DATE 11/19/13	ACCOUNT BL2204	TRUCK 0131	DRIVER BEN JONES	TICKET 2038978
CUSTOMER NAME BLISS SPORTS, L.C.				DELIVERY ADDRESS ROCK CHALK PARK 9+ ENTER AT G-WILLIAMS		
PURCHASE ORDER NOT GEO.	SALES ORDER	TAX 6.8	CREDIT 2			SLUMP 2.00 in
LOAD QTY. 7.00	PRODUCT 156421	DESCRIPTION KCPMB 4K	ORDERED 25.00	DELIVERED 25.00	UNIT PRICE	AMOUNT

WINTER SERVICE

LOADED 10:06	ARRIVE JOB SITE 10:39	START DISCHARGE 10:41	FINISH DISCHARGE 11:41	ARRIVE PLANT 12:21
-----------------	--------------------------	--------------------------	---------------------------	-----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB →	Gallons <i>2</i>	By
--	---------------------------------	---------------------	----

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eye, rinse immediately and repeatedly with water and get prompt medical attention.
KEEP OUT OF REACH OF CHILDREN

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP EXTRA CHARGE FOR OVER 30 MINUTES →
RECEIVED IN GOOD CONDITION BY <i>[Signature]</i>

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line.
If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0131	022	user		2038978	94401	10:06	11/19/13
Load Size	Mix Code	Returned	Qty	Mix	Age	Seq	Load ID
7.00	CYDS 156421					W	96419
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.70 GL	158.36 GL	154.00 GL	-2.75%		154.00 gl	
ADVA140	16.50 OZ	115.50 OZ	115.00 OZ	-0.43%			
PVCA-5	1620 LB	11425 LB	11440 LB	0.13%	0.75% M	10 gl	
JPSAND	1325 LB	9407 LB	9400 LB	-0.07%	2.20% A	25 gl	
CENTRAL	450.0 LB	3150.0 LB	3160.0 LB	0.32%			
LAFGBFS	150.0 LB	1050.0 LB	1045.0 LB	-0.40%			
DARA1400	5.00 OZ	35.00 OZ	35.00 OZ	0.00%			
Actual	Num Batches: 1				Manual 10:06:25		
Load Total:	26420 lb	Design 0.441	Water/Cement 0.440 T		Design 221.9 gl	Actual 189.5 gl	To Add: 32.4 gl
Slump:	2.00 in	Water in Truck: 0.0 GL	Adjust Water: 0.0 GL / Load		Trim Water: -2.0 GL/ CYD		

OFFICE ORIGINAL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/20/2013	BLISS	0194	Mark Ice	1090917

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOBSITE - NORTH ON CONCRETE HAUL RD - BACKUP TO PAVER SOUTH OF SOCCER FIELD



38,194

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
34	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	195	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	300	300		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	14400		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUEINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

_____ X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME TITLE

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	12.50 oz	125.00 oz	125.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4515 lb	0.33%				
ROCKGMKC	1622 lb	16463 lb	16650 lb	> 1.13%	1.50% M	29	gl	
SANDFAA	1327 lb	13774 lb	13870 lb	0.70%	3.80% M	61	gl	
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WATER	30.2 gl	192.4 gl	192.0 gl	-0.22%		192.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
DARASET	48.00 oz	480.00 oz	480.00 oz	0.00%				

Manual 15:42:11
 Num Batches: 1
 ual 38194 lb Design W/C: 0.420 Water/Cement: 0.419 T Design 302.0 gl Actual 282.3 gl To Add: 19.7 gl
 id 1.50 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT
 mp:



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/22/2013	BLISS	0139	Kevin Tolbert	1090936

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAMS WAY NORTH -
JOB ADDRESS	WEST ONTO JOBSITE - PAST WASHOUT ON NORTH
6100 ROCK CHALK DR - ROCK CHALK	SIDE - BACKUP TO PAVER
PARK - LAWRENCE, KS	

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
36	TEC#	ROCKCHALKPAR		HANDPAV	194	5
	000003471					
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	17	17		
8.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
		TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	
	ARRIVE PLANT	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

_____ X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	13236 lb	13250 lb	0.11%	1.50% M	23	gl	
SANDFAA	1332 lb	11061 lb	11110 lb	0.44%	3.80% M	49	gl	
CEMENT	450 lb	3600 lb	3705 lb	+ 2.92%				
SLAG	150 lb	1200 lb	1210 lb	0.83%				
WREDUCE1	30.00 oz	240.00 oz	240.00 oz	0.00%				
AIR1	6.50 oz #	52.00 oz	52.00 oz	0.00%				
WATER	30.9 gl	159.2 gl	159.0 gl	-0.15%		159.0	gl	-2.00 gl

Num Batches: 1
 Design 247.2 gl Actual 231.2 gl To Add: 16.0 gl
 Design WC: 0.430 Water/Cement: 0.420 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT
 Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	11/25/2013	BLISS	0194	Mark Ice	1091006

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAMS WAY NORTH -
JOB ADDRESS	WEST ONTO JOBSITE - FOLLOW DIRT ROAD NEXT TO
6100 ROCK CHALK DR - ROCK CHALK	NEW PAVEMENT TO GET TO PAVER
PARK - LAWRENCE, KS	



37,952

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
6	TEC# 000003471	ROCKCHALKPAR		MAINLINE	151	1.5
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	550	530		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	25440		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water, if any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME TITLE

X

CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	12.00 oz	120.00 oz	120.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4515 lb	0.33%				
ROCKGMKC	1622 lb	16398 lb	16420 lb	0.13%	1.10% M	21	gl	
SANDFAA	1327 lb	13683 lb	13690 lb	0.05%	3.11% A	49	gl	
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WATER	30.2 gl	211.2 gl	211.0 gl	-0.08%		211.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	301.00 oz	0.33%				
DARASET	48.00 oz	480.00 oz	480.00 oz	0.00%				

Num Batches: 1 Manual 16:34:13

Design 302.0 gl Actual 281.9 gl To Add: 20.1 gl

Water/Cement: 0.418 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT

Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
 SHAWNEE MISSION, KANSAS 66227-2705
 DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
 (800) 322-9710 (800) 524-6474



American Concrete Institute
 Certifications



Certifications

KANSAS
 DEPARTMENT OF TRANSPORTATION
 Certifications

www.pennysconcrete.com
 An Equal Opportunity Employer

PLANT 01	DATE 11/26/2013	ACCOUNT BLISS	TRUCK 0127	DRIVER NAME BEN JARVIS	TICKET # 1091031
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOBSITE - PAST WASHOUT ON NORTH SIDE - BACKUP TO PAVER		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		



37,916

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
5	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	194	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	80	60		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	2880		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

SUBTOTAL
 TAX
 TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY

_____ X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
AIR1	12.50 oz	125.00 oz	125.00 oz	0.00%				
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
ROCKGMKC	1622 lb	16366 lb	16370 lb	0.02%	0.90% M	17	gl	
SANDFAA	1327 lb	13696 lb	13710 lb	0.10%	3.21% A	51	gl	
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WATER	30.2 gl	213.5 gl	212.0 gl	-0.70%		212.0	gl	-2.00 gl
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
DARASET	48.00 oz	480.00 oz	480.00 oz	0.00%				

Num Batches: 1
 Manual 12:23:25
 ual 37916 lb Design W/C: 0.420 Water/Cement: 0.419 T Design 302.0 gl Actual 280.6 gl To Add: 21.4 gl
 id mp: 1.50 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 15:10	DATE 11/26/13	ACCOUNT BL2204	TRUCK 0093	DRIVER WES SCHMITT	TICKET 2039278
CUSTOMER NAME BLISS SPORTS, L.C.				DELIVERY ADDRESS 6TH & GEORGE WILLIAMS WAY TH LOOK FOR SUNFLOWERS CURB MACHINE		
PURCHASE ORDER ROCK CHAL		SALES ORDER	TAX 68	CREDIT 2	SLUMP 2.00 in	

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	156421	KCMMB 4K	38.00	38.00		

WINTER SERVICE

LOADED 14:39	ARRIVE JOB SITE 3:06	START DISCHARGE 3:21	FINISH DISCHARGE 4:23	ARRIVE PLANT 4:43
-----------------	-------------------------	-------------------------	--------------------------	----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB →	Gallons 0	By
--	---------------------------------	--------------	----

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP EXTRA CHARGE FOR OVER 30 MINUTES →
--

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eye, rinse immediately and repeatedly with water and get prompt medical attention.
KEEP OUT OF REACH OF CHILDREN

RECEIVED IN GOOD CONDITION BY X

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line.
If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0093	232	user	2039278		94696	14:39	11/26/13
Load Size	Mix Code	Returned	Qty	Mix	Age	Seq	Load ID
10.00 CYDS	156421					W	96719
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.70 GL	211.06 GL	210.00 GL	-0.50%		210.00 gl	
ADVA140	16.50 OZ	165.00 OZ	165.00 OZ	0.00%			
FVCA-5	1620 LB	16322 LB	16360 LB	0.24%	0.75% M	15 gl	
JPSAND	1325 LB	13679 LB	13640 LB	-0.28%	3.24% A	51 gl	
CENTRAL	450.0 LB	4500.0 LB	4465.0 LB	-0.78%			
LAFGBBFS	150.0 LB	1500.0 LB	1490.0 LB	-0.67%			
DARA1400	5.00 OZ	50.00 OZ	50.00 OZ	0.00%			
Actual	Num Batches: 1						
Load Total:	37721 lb	Design 0.441	Water/Cement 0.444 T		Manual 14:39:17	Design 317.0 gl	Actual 275.8 gl To Add: 41.2 gl
Slump:	2.00 in	# Water in Truck: 0.0 GL	Adjust Water: 0.0 GL / Load	Trim Waters: -2.0 GL/ CYD	Note: Manual feed ok		

OFFICE ORIGINAL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 11/29/2013	ACCOUNT BLISS	TRUCK 0194	DRIVER NAME Mark Ice	TICKET # 1091080
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOBSITE - BACK UP TO PAVER		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		



38,164

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
11	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	139	1.5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	160	140		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	6720		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	16350 lb	16360 lb	0.06%	0.80% M	16	gl	
SANDFAA	1327 lb	13655 lb	13810 lb	+ 1.13%	2.90% A	47	gl	
CEMENT	450 lb	4500 lb	4595 lb	+ 2.11%				
SLAG	150 lb	1500 lb	1515 lb	1.00%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	12.00 oz #	120.00 oz	120.00 oz	0.00%				
WATER	30.2 gl	220.3 gl	219.0 gl	-0.57%		219.0	gl	-2.00 gl
DARASET	48.00 oz	480.00 oz	480.00 oz	0.00%				

Manual 13:27:04

Num Batches: 1

Design 302.0 gl Actual 281.3 gl To Add: 20.7 gl

Water/Cement: 0.413 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYT

Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 11/30/2013	ACCOUNT BLISS	TRUCK 0114	DRIVER NAME BRIAN LINDELOF	TICKET # 1091090	
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOB SITE -HAUL RD NORTH - BACK TO THE EASTAT FIRST CONCRETE RD TO JOB			
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS						
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!			
ORDER # 7	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION HANDPAV	PREVIOUS TRUCK 139	SLUMP 5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	80	80		
10.00	ea	SATDC	SATURDAY DELIVERY CHAF	0			
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds ___ gal ___ yds ___ gal ___ yds ___ gal ___ yds ___ gal ___

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

GRAND TOTAL
MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16414 lb	16440 lb	0.16%	0.70% M	14	gl	
SANDFAA	1332 lb	13731 lb	13750 lb	0.14%	3.09% A	49	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	6.00 oz #	60.00 oz	59.00 oz	-1.67%				
WATER	30.9 gl	226.0 gl	226.0 gl	-0.01%		226.0	gl	-2.00 gl

Num Batches: 1 Manual 12:20:46

Design 309.0 gl Actual 289.1 gl To Add: 19.9 gl

38108 lb Design W/C: 0.430 Water/Cement: 0.429 T Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC

5.00 in # Water in Truck: 0.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	12/02/2013	BLISS	0135	KENNETH NICHOLS	1091121
CUSTOMER NAME			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
BLISS SPORTS LLC			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH -		
JOB ADDRESS			WEST ONTO JOB SITE -HAUL RD NORTH TO JOB		
6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE:		
30,494			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
46	TEC# 000003471 8	ROCKCHALKPAR		HANDPAV	146	5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	58	58		
8.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C136. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

_____ X _____
PRINTED NAME TITLE CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	13131 lb	13170 lb	0.29%	0.70% M	11	gl	
SANDFAA	1332 lb	10933 lb	10930 lb	-0.02%	2.60% A	33	gl	
CEMENT	450 lb	3600 lb	3605 lb	0.14%				
SLAG	150 lb	1200 lb	1210 lb	0.83%				
WREDUCE1	30.00 oz	240.00 oz	240.00 oz	0.00%				
AIR1	6.00 oz #	48.00 oz	48.00 oz	0.00%				
WATER	30.9 gl	187.1 gl	187.0 gl	-0.06%		187.0	gl	-2.00 gl

Num Batches: 1 Manual 16:15:17
 30494 lb Design W/C: 0.430 Water/Cement: 0.428 T Design 247.2 gl Actual 231.1 gl To Add: 16.1 gl
 5.00 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYL

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 10:18	DATE 12/02/13	ACCOUNT BL2204	TRUCK 0126	DRIVER KEN TEICHMANN	TICKET 2039343
CUSTOMER NAME BLISS SPORTS, L.C.			DELIVERY ADDRESS 6TH & GEORGE WILLIAMS WAY TH			
PURCHASE ORDER ROCK CHAL.	SALES ORDER	TAX 6.0	CREDIT 2			SLUMP 2.00 in
LOAD QTY. 7.00	PRODUCT 156421	DESCRIPTION KCMME 4K	ORDERED 15.00	DELIVERED 15.00	UNIT PRICE	AMOUNT

WINTER SERVICE

LOADED 9:46	ARRIVE JOB SITE 10:14	START DISCHARGE 10:25	FINISH DISCHARGE 11:30	ARRIVE PLANT 12:12
----------------	--------------------------	--------------------------	---------------------------	-----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB →	Gallons 3	By
--	---------------------------------	--------------	----

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP EXTRA CHARGE FOR OVER 30 MINUTES →
--

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact when possible and wash exposed skin areas promptly with water. If any cementitious material gets into the eye, rinse immediately and repeatedly with water and get prompt medical attention.
KEEP OUT OF REACH OF CHILDREN

RECEIVED IN GOOD CONDITION BY X

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line. If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0126	112	user	2039343	94761	94761	9:46	12/2/13
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID	
7.00 CYDS	156421				W	96784	
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.78 GL	152.69 GL	152.00 GL	-0.45%		152.00 gl	
ADVA140	16.58 OZ	115.50 OZ	115.00 OZ	-0.43%			
PVCA-5	1620 LB	11425 LB	11440 LB	0.13%	0.75% M	10 gl	
JPSAND	1325 LB	9534 LB	9400 LB	-0.56%	2.79% A	31 gl	
CENTRAL	450.0 LB	3150.0 LB	3155.0 LB	0.16%			
LAFGBBFS	150.0 LB	1050.0 LB	1040.0 LB	-0.95%			
DARA1400	5.00 OZ	35.00 OZ	35.00 OZ	0.00%			
Actual	Num Batches: 1				Manual 9:46:03		
Load Total: 26393 lb	Design 0.441	Water/Cement 0.441 T			Design 221.9 gl	Actual 193.8 gl	To Add: 28.9 gl
Slump: 2.00 in	# Water in Truck: 0.0 GL	Adjust Water: 0.0 GL	/ Load	Trim Water: -2.0 GL/ CYD			

MCM Midwest Concrete Materials, Inc.

3645 E. 23rd Street • Lawrence, KS 66046
(785) 843-1688 • FAX (785) 843-1783

LAWRENCE (785) 843-1688 • TOLL FREE (888) 244-2082

"QUALITY AND SERVICE SINCE 1927"

PLANT 20	TIME 19:54	DATE 12/02/13	ACCOUNT BL2204	TRUCK 0133	DRIVER CALEB RICKETTS	TICKET 2039407
CUSTOMER NAME BLISS SPORTS, L.C.				DELIVERY ADDRESS 6TH & GEORGE WILLIAMS WAY TH		
PURCHASE ORDER ROCK CHAL.		SALES ORDER	TAX 60	CREDIT 2	SLUMP 1.25 in	

LOAD QTY.	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	156421	KCMB 4K	100.00	100.00		
1.00	5105	LATE DELIVERY CHARGE	4.00	4.00		
164.00	1900	Unloading Charge				

WINTER SERVICE

LOADED 19:10	ARRIVE JOB SITE 7:49	START DISCHARGE 9:58	FINISH DISCHARGE 11:03	ARRIVE PLANT 11:25
-----------------	-------------------------	-------------------------	---------------------------	-----------------------

SUB TOTAL
DISCOUNT
TAX
TOTAL
PREVIOUS TOTAL
GRAND TOTAL

This batch of concrete is mixed with the proper amount of water. If additional water is desired, please instruct the driver.	ADDITIONAL WATER ADDED ON JOB →	Gallons 80	By
--	---------------------------------	---------------	----

UNLOADING TIME ALLOWED 30 MINUTES PER TRIP EXTRA CHARGE FOR OVER 30 MINUTES →
RECEIVED IN GOOD CONDITION BY X

CAUTION: Freshly mixed cement, mortar, grout or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water.
If any combustible material gets into the eye, rinse immediately and repeatedly with water and get prompt medical attention.
KEEP OUT OF REACH OF CHILDREN

Purchaser waives all claims for personal or property damage caused by seller's truck when delivery is made beyond street curb line.

If not paid as agreed, this credit agreement provides for your payment of reasonable costs of collection, including, but not limited to, court costs, attorney fees and/or collection agency fees.

Truck	Driver	User	Disp	Ticket Num	Ticket ID	Time	Date
0133	030	user		2039407	94024	19:10	12/2/13
Load Size	Mix Code	Returned	Qty	Mix	Age	Seq	Load ID
10.00 CYDS	156421					W	96848
Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	
WATER	31.70 GL	280.07 GL	285.00 GL	-1.40%		285.00 gl	
ADVA140	16.50 OZ	165.00 OZ	165.00 OZ	0.00%			
PVCA-5	1620 LB	16322 LB	16340 LB	0.11%	0.75% W	15 gl	
JPSAND	1325 LB	13641 LB	13648 LB	-0.01%	2.95% A	47 gl	
CENTRAL	450.0 LB	4500.0 LB	4470.0 LB	-0.67%			
LAFGBFS	150.0 LB	1500.0 LB	1490.0 LB	-0.67%			
DARA1400	5.00 OZ	50.00 OZ	50.00 OZ	0.00%			
Actual	Num Batches:	1			Manual	19:18:34	
Load Total:	37664 lb	Design 0.441	Water/Cement 0.444 T		Design 317.0 gl	Actual 266.4 gl	To Adds 50.6 gl
Slump:	1.25 in	W	Water in Truck: 0.0 GL	Adjust Water: 0.0 GL	/ Load	Trim Water: -2.0 GL/ CYB	

OFFICE ORIGINAL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com

An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	12/03/2013	BLISS	0174	Shawn Cool	1091141
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOBSITE - PAST WASHOUT ON NORTH SIDE - BACKUP TO PAVER		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
73	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	152	5

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	90	20		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO		
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal				TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.
 MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16414 lb	16520 lb	0.65%	0.70% M	14	gl	
SANDFAA	1332 lb	13716 lb	13720 lb	0.03%	2.97% A	47	gl	
CEMENT	450 lb	4500 lb	4530 lb	0.67%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	6.25 oz #	62.50 oz	62.00 oz	-0.80%				
WATER	30.9 gl	227.9 gl	226.0 gl	-0.82%		226.0	gl	-2.00 gl

Num Batches: 1 Manual 15:00:23

Design 309.0 gl Actual 287.2 gl To Add: 21.8 gl

Design Water/Cement 0.427 T Trim Water: -2.00 / CY

Water in Truck: 0.0 gl



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	12/04/2013	BLISS	0159	DOUG BERG	1091175		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOBSITE - HAUL RD NORTH TO PUMP				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
57	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	184	5	
38,215							
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	60	40		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME TITLE

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16414 lb	16460 lb	0.28%	0.70% M	14	gl	
SANDFAA	1332 lb	13767 lb	13800 lb	0.24%	3.36% A	54	gl	
CEMENT	450 lb	4500 lb	4580 lb	+ 1.78%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	6.00 oz #	60.00 oz	61.00 oz	1.67%				
WATER	30.9 gl	221.7 gl	222.0 gl	0.13%		222.0	gl	-2.00 gl

ual Num Batches: 1 Manual 10:51:14
id 38215 lb Design W/C: 0.430 Water/Cement: 0.424 T Design 309.0 gl Actual 289.5 gl To Add: 19.5 gl
mp: 5.00 in # Water in Truck: 0.0 gl Just Water: 0.0 gl / Load Trim Water: -2.00 / CY



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
 SHAWNEE MISSION, KANSAS 66227-2705
 DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
 (800) 322-9710 (800) 524-6474

www.pennysconcrete.com
 An Equal Opportunity Employer



American Concrete Institute®
 Certifications



Certifications

KANSAS
 DEPARTMENT OF TRANSPORTATION
 Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	12/17/2013	BLISS	0114	BRIAN LINDELOF	1091370

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAM WAY NORTH -
JOB ADDRESS	WEST THROUGH GATE - NORTH ON CONCRETE HAUL
ROCK CHALK PARK - REC. & WELNESS	RD - WEST AT END TO PAVING
CENTER - LAWRENCE, KS - SUNFLOW	



38,062

NOTE:
 ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
 STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
13		ROCKCHALKREC		MAINLINE	174	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	300	150		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
 TAX
 TOTAL
 GRAND TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

 PRINTED NAME TITLE
 X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16349 lb	16340 lb	-0.05%	0.30% M	6	gl	
SANDFAA	1332 lb	13706 lb	13720 lb	0.10%	2.90% M	46	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	6.00 oz #	60.00 oz	60.00 oz	0.00%				
WATER	30.9 gl	238.9 gl	236.0 gl	-0.36%		236.0	gl	-2.00 gl

ual Num Batches: 1 Manual 14:18:53
 id 38062 lb Design W/C: 0.430 Water/Cement: 0.429 T Design 309.0 gl Actual 288.2 gl To Add: 20.8 gl
 mp: 4.00 in Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
Department of Transportation
Certifications

PLANT 01	DATE 12/18/2013	ACCOUNT BLISS	TRUCK 0133	DRIVER NAME LANCE DAY	TICKET # 1091472		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - WEST THROUGH GATE - NORTH ON CONCRETE HAUL RD - WEST AT END TO PAVING				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS - SUNFLOW			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
			38,161				
ORDER # 75	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION EXTFW	PREVIOUS TRUCK 184		
SLUMP 4							
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	400	356		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.
MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16349 lb	16450 lb	0.62%	0.30% M	6	gl	
SANDFAA	1332 lb	13759 lb	13760 lb	0.00%	3.30% A	53	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER	30.9 gl	230.5 gl	230.0 gl	-0.21%		230.0	gl	-2.00 gl

Num Batches: 1
Manual 15:54:19
Design W/C: 0.430 Water/Cement: 0.429 T Design 309.0 gl Actual 288.6 gl To Add: 20.4 gl
Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 12/19/2013	ACCOUNT BLISS	TRUCK 0159	DRIVER NAME DOUG BERG	TICKET # 1091507		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - WEST THROUGH GATE - NORTH ON CONCRETE HAUL RD - WEST AT END TO PAVING				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS - SUNFLOW							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER # 34	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION HANDPAV	PREVIOUS TRUCK 135	SLUMP 4	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	250	200		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal				TOTAL
				GRAND TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16349 lb	16350 lb	0.01%	0.30% M	6	gl	
SANDFAA	1332 lb	13756 lb	13750 lb	-0.05%	3.28% A	52	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1515 lb	1.00%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	4.75 oz #	47.50 oz	48.00 oz	1.05%				
WATER	30.9 gl	230.9 gl	231.0 gl	0.06%		231.0	gl	-2.00 gl

ual Num Batches: 1 Manual 12:24:08

id 38074 lb Design W/C: 0.430 Water/Cement: 0.428 T Design 309.0 gl Actual 289.1 gl To Add: 19.9 gl

mp: 4.00 in Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CY



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	02/22/2014	BLISS	0112	KEITH STAMBAUGH	1092161
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ONTO JOBSITE - FOOTING AT FAR WEST SIDE OF PROJECT		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
6	TEC# 000003471 8	ROCKCHALKPAR		PAVING	139	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	50	30		
10.00	ea	SATDC	SATURDAY DELIVERY CHAF	0			
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

GRAND TOTAL
MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE _____
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16333 lb	16360 lb	0.17%	0.20% M	4	gl	
SANDFAA	1332 lb	13721 lb	13720 lb	-0.01%	3.01% A	48	gl	
CEMENT	450 lb	4500 lb	4540 lb	0.89%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	5.50 oz #	55.00 oz	56.00 oz	1.82%				
WATER	30.9 gl	237.0 gl	237.0 gl	0.01%		237.0	gl	-2.00 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	02/24/2014	BLISS	0173	Marty Trumble	1092224

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAMS WAY NORTH
JOB ADDRESS	UNTIL IT CURVES - NORTHON HAUL RD - WEST AT
6100 ROCK CHALK DR - ROCK CHALK	END TO NORWEST SIDE OF BUILDING - BACK DOWN
PARK - LAWRENCE, KS	FIRST DIRT LANE

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
72	TEC# 000003471 8	ROCKCHALKPAR		HANDPAV	192	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	60	60		
10.00	oz	DARASET	DARASET 1.0% NON-CHLOF	1	5760		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	BEFORE H2O ADDED
		<input type="checkbox"/> YES <input type="checkbox"/> NO	<input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds ___ gal ___ yds ___ gal ___ yds ___ gal ___ yds ___ gal ___

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery; if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16365 lb	16390 lb	0.15%	0.40% M		8 gl	
SANDFAA	1332 lb	13716 lb	13710 lb	-0.05%	2.97% A		47 gl	
CEMENT	450 lb	4500 lb	4520 lb	0.44%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	301.00 oz	0.33%				
AIR1	5.20 oz #	52.00 oz	52.00 oz	0.00%				
WATER	30.9 gl	233.7 gl	234.0 gl	0.13%		234.0	gl	-2.00 gl
DARASET	96.00 oz	960.00 oz	944.00 oz	-1.67%				



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute*
Certifications




Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/10/2014	BLISS	0184	Shawn Cool	1092324

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WILL TURN WEST - NORTH ON HAUL RD - WEST AT END TO PAVING AT NORTH END OF TRACK
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	

	38,089	NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!
---	--------	--

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
9	TEC# 000003471 8	ROCKCHALKPAR		HANDPAV	159	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	120	110		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

GRAND TOTAL

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X _____
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16333 lb	16370 lb	0.23%	0.20% M	4	gl	
SANDFAA	1332 lb	13616 lb	13610 lb	-0.04%	2.22% A	35	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	249.6 gl	249.0 gl	-0.26%		249.0	gl	-2.00 gl

Num Batches: 1 Manual 10:07:28

Design W/C: 0.430 Water/Cement 0.429 T Design 309.0 gl Actual 288.4 gl To Add: 20.6 gl

Water in Truck: 0.0 gl Just Water: 0.0 gl / Load Trim Water: -2.0 / CYL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/10/2014	BLISS	0157	JOHN BOLEY	1092349
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WILL TURN WEST - SOUTH ON HAUL RD - THEN BACK TO CREW		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
56	TEC# 000003471 8	ROCKCHALKPAR		HANDPAV	194	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	60	40		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKG MKC	1630 lb	16365 lb	16370 lb	0.03%	0.40% M		8 gl	
SANDFAA	1332 lb	13640 lb	13660 lb	0.15%	2.40% M		38 gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	242.9 gl	243.0 gl	0.05%		243.0 gl		-2.00 gl

Num Batches: 1

Manual 15:01:08

id 38089 lb Design W/C: 0.430 Water/Cement 0.429 T Design 309.0 gl Actu 289.2 gl To Add: 19.8 gl

mp: 4.00 in Water in Truck: 0.0 gl Just Water: 0.0 gl / Load Trim Water: -2.0 / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/11/2014	BLISS	0193	Robert Crosby	1092370
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WILL TURN WEST - NORTH ON HAUL RD - WEST AT END TO PAVING AT NORTH END OF TRACK		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
15	TEC# 000003471 8	ROCKCHALKPAR		HANDPAV	114	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	250	50		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
8:15			
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wt	Trim
ROCKGMKC	1630 lb	16333 lb	16390 lb	0.35%	0.20% M	4	gl	
SANDFAA	1332 lb	13632 lb	13710 lb	0.57%	2.34% A	38	gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%				
SLAG	150 lb	1500 lb	1520 lb	+ 1.33%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	4.20 oz #	42.00 oz	41.00 oz	-2.38%				
WATER	30.9 gl	247.7 gl	247.0 gl	-0.27%		247.0	gl	-2.00 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute®
Certifications




Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/13/2014	BLISS	0160	Joseph Tate	1092467

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - POURING HAND CURB ON THE SOUTHWEST CORNER OF PARKING JUST NORTH OF JOB TRAILER
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	

	30,312	NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!
---	--------	---

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
44	TEC# 000003471 8	ROCKCHALKPAR		MACHINE	145	1.25

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K .42 25%	43	43		
8.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

X

CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	W/C	Trim
ROCKGMKC	1822 lb	13067 lb	13070 lb	0.02%	0.70% M	11	gl	
SANDFAA	1327 lb	10924 lb	10990 lb	0.61%	2.90% A	37	gl	
CEMENT	450 lb	3600 lb	3610 lb	0.28%				
SLAG	150 lb	1200 lb	1205 lb	0.42%				
WREDUCE1	30.00 oz	240.00 oz	240.00 oz	0.00%				
AIR1	7.00 oz #	56.00 oz	56.00 oz	0.00%				
WATER	30.2 gl	169.9 gl	170.0 gl	0.09%		170.0	gl	-3.00 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/14/2014	BLISS	0194	Wayne Grammer	1092496

CUSTOMER NAME	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS
BLISS SPORTS LLC	6TH ST. WEST - GEORGE WILLIAMS WAY NORTH -
JOB ADDRESS	WILL TURN WEST - SOUTH ON HAUL RD - THEN
6100 ROCK CHALK DR - ROCK CHALK	BACK TO CREW
PARK - LAWRENCE, KS	

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
53	TEC#	ROCKCHALKPAR		HANDCURB	193	3
	000003471					
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	64	26		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

_____ X _____
 PRINTED NAME TITLE CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wet	Trim
ROCKG MKC	1630 lb	16398 lb	16400 lb	0.01%	0.60% M	12	gl	
SANDFAA	1332 lb	13623 lb	13650 lb	0.20%	2.28% A	36	gl	
CEMENT	450 lb	4500 lb	4515 lb	0.33%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	241.0 gl	241.0 gl	0.02%		241.0	gl	-2.00 gl

PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 03/14/2014	ACCOUNT BLISS	TRUCK 0145	DRIVER NAME Steve Wilson	TICKET # 1092540		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - WEST THROUGH GATE PASTOLD WASHOUT PIT - NORTH TOWARDSTRACK - BACKUP EAST TO PAVER				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS -							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER # 116	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK 149		
SLUMP 4							
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	60	50		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	5		
10.00	oz	RETARD	WR GRACE RECOVER RETAF	1	450		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO
			<input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16398 lb	16410 lb	0.07%	0.60% M	12	gl	
SANDFAA	1332 lb	13592 lb	13600 lb	0.06%	2.05% A	33	gl	
CEMENT	450 lb	4500 lb	4515 lb	0.33%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	244.6 gl	245.0 gl	0.15%		245.0	gl	-2.00 gl
RETARD	9.00 oz	90.00 oz	90.00 oz	0.00%				

Num Batches: 1 Manual 15:43:37

Design W/C: 0.430 Water/Cement: 0.428 T Design 309.0 gl Actual 289.4 gl To Add: 19.6 gl

Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
Department of Transportation
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/15/2014	BLISS	0139	Kevin Tolbert	1092549
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - WEST ON CONCRETE RD AT SOUTH END OF PROJECT TO JOB		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
14	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	113	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	70	70		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	7		
10.00	ea	SATDC	SATURDAY DELIVERY CHAR	0			
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	SUBTOTAL TAX TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wt	Trim
ROCKGMKC	1630 lb	16365 lb	16390 lb	0.15%	0.40% M	8	gl	
SANDFAA	1332 lb	13846 lb	13850 lb	0.03%	2.44% A	39	gl	
CEMENT	450 lb	4500 lb	4500 lb	0.00%				
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	242.2 gl	243.0 gl	0.34%		243.0	gl	-2.00 gl

Num Batches: 1 Manual 9:10:37
 Design W/C: 0.430 Water/Cement 0.429 T Design 309.0 gl Actual 289.9 gl To Add: 19.1 gl
 Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.00 gl / CYT



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute*
Certifications




Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/18/2014	BLISS	0195	Marty Trumble	1092615

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - POURING INPARKING LOT JUST NORTH OF JOB TRAILER
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	

	38,211	NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!
---	--------	---

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
38	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	139	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	110	90		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	9		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16333 lb	16350 lb	0.11%	0.20% M	4	gl	
SANDFAA	1332 lb	13879 lb	13700 lb	0.15%	2.70% A	43	gl	
CEMENT	450 lb	4500 lb	4600 lb	+ 2.22%				
SLAG	150 lb	1500 lb	1520 lb	+ 1.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	41.00 oz	-2.38%				
WATER	30.9 gl	242.0 gl	242.0 gl	-0.01%		242.0	gl	-2.00 gl

ual Num Batches: 1 Manual 13:36:02
id 38211 lb Design W/C: 0.430 Water/Cement 0.421 T Design 309.0 gl Act 289.1 gl To Add: 20.0 gl
mp: 4.00 in Water in Truck: 0.0 gl just Water: 0.0 gl / Load Trim Water: -2.0 / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/19/2014	BLISS	0194	Wayne Grammer	1092649
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH - WEST ON RAMP BETWEEN SOCCER AND SOFTBALL FIELD		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
47	TEC# 000003471 8	ROCKCHALKPAR		MACHINE		1.25

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
9.00	yd	AS6425G4	KCMMB 4K .42 25%	18	9		
9.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1622 lb	14642 lb	14660 lb	0.12%	0.30% M		5 gl	
SANDFAA	1327 lb	12273 lb	12350 lb	0.63%	2.77% A		40 gl	
CEMENT	450 lb	4050 lb	4050 lb	0.00%				
SLAG	150 lb	1350 lb	1350 lb	0.00%				
WREDUCE1	30.00 oz	270.00 oz	269.00 oz	-0.37%				
AIR1	5.20 oz #	46.80 oz	46.00 oz	-1.71%				
WATER	30.2 gl	200.0 gl	199.0 gl	-0.49%		199.0 gl		-3.00 gl

Num Batches: 1 Manual 15:38:45
 id 34090 lb Design W/C: 0.420 Water/Cement 0.420 T Design 271.8 gl Ac 244.1 gl To Add: 27.7 gl
 mp: 1.25 in # Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -3.00 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 03/20/2014	ACCOUNT BLISS	TRUCK 0139	DRIVER NAME Kevin Tolbert	TICKET # 1092665
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH - WEST ON RAMP BETWEEN SOCCER AND SOFTBALL FIELD		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER # 38	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK 152	SLUMP 4
---------------	-------------------------------	------------------------------	------	------------------------	-----------------------	------------

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	40	40		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	4		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wet	Trim
ROCKGMKC	1630 lb	16365 lb	16370 lb	0.03%	0.40% M	8	gl	
SANDFAA	1332 lb	13613 lb	13690 lb	0.57%	2.20% M	35	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	246.1 gl	245.0 gl	-0.44%		245.0	gl	-2.00 gl

Num Batches: 1

Manual 9:00:40

id 38136 lb Design W/C: 0.430 Water/Cement 0.429 T Design 309.0 gl Act 288.1 gl To Add: 20.9 gl

mp: 4.00 in Water in Truck: 0.0 gl just Water: 0.0 gl / Load Trim Water: -2.00 / CYT



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	03/20/2014	BLISS	0129	THOMAS OHM	1092686		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH - WEST ON RAMP BETWEEN SOCCER AND SOFTBALL FIELD				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
38	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	139	4	
38,191							
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	110	110		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	11		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16365 lb	16450 lb	0.52%	0.40% M		8 gl	
SANDFAA	1332 lb	13643 lb	13640 lb	-0.02%	2.42% A		39 gl	
CEMENT	450 lb	4500 lb	4555 lb	+ 1.22%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	41.00 oz	-2.38%				
WATER	30.9 gl	242.5 gl	242.0 gl	-0.20%		242.0 gl		-2.00 gl

Num Batches: 1 Manual 14:42:29
 id 38191 lb Design W/C: 0.430 Water/Cement 0.426 T Design 309.0 gl Act 288.5 gl To Add: 20.5 gl
 mp: 4.00 in Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.00 gl / CYC



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	03/20/2014	BLISS	0113	DOUG BERG	52000122		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - TURN WEST INTO PARKING LOT JUST SOUTH OF SOCCER FIELD				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO# OR JOB#	APPLICATION	ZONE CODE	PREVIOUS TRUCK	SLUMP		
42	TEC# 0000034718	HANDCURB	LAW	152	3		
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	CYDS	AS6425G4	KCMMB 4K 25% .44	30	15		
8.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

8"
7.0"
41"
1:45

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

X
CUSTOMER SIGNATURE

PRINTED NAME _____ TITLE _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Truck	Driver	User	Disp Ticket Num	Ticket ID	Time	Date
113	1035	buds	52000122	239	12:34	3/20/14
Load Size	Mix Code	Returned	Qty	Mix Age	Seq	Load ID
.00	CYDS AS6425G44				W2	319

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGKMC	1630 lb	13079 lb	13120 lb	0.31%	0.30% M	5	gal	
SANDFAA	1332 lb	11104 lb	11120 lb	0.15%	4.20% M	54	gal	
CEMENT	450.0 lb	3600.0 lb	3625.0 lb	0.69%				
SLAG	150.0 lb	1200.0 lb	1210.0 lb	0.83%				
WREDUCE1	30.00 oz	240.00 oz	240.00 oz	0.00%				
AIR1	4.20 oz #	33.60 oz	33.00 oz	-1.79%				
WATER	30.9 gl	156.9 gl	152.0 gl	-3.11%		152.0	gal	-3.00 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/21/2014	BLISS	0195	Marty Trumble	1092734
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - TURN WEST INTO PARKING LOT JUST SOUTH OF SOCCER FIELD		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
66	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	138	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	100	60		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	6		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS:		BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16333 lb	16380 lb	0.29%	0.20% M	4	gl	
SANDFAA	1332 lb	13720 lb	13720 lb	0.00%	3.00% A	48	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	301.00 oz	0.33%				
AIR1	4.30 oz #	43.00 oz	42.00 oz	-2.33%				
WATER	30.9 gl	237.2 gl	237.0 gl	-0.08%		237.0	gl	-2.00 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 03/25/2014	ACCOUNT BLISS	TRUCK 0193	DRIVER NAME Robert Crosby	TICKET # 1092834
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TO SIDEWALK ON WEST SIDE OF GEORGE WILLIAMS WAY		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER # 16	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK 171	SLUMP 4
---------------	-------------------------------	------------------------------	------	------------------------	-----------------------	------------

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	120	60		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	6		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 19:52	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16316 lb	16340 lb	0.15%	0.10% M	2	gl	
SANDFAA	1332 lb	13662 lb	13660 lb	-0.01%	2.57% A	41	gl	
CEMENT	450 lb	4500 lb	4520 lb	0.44%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER	30.9 gl	246.1 gl	246.0 gl	-0.03%		246.0	gl	-2.00 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 03/25/2014	ACCOUNT BLISS	TRUCK 0193	DRIVER NAME Robert Crosby	TICKET # 1092824
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH - WEST THROUGH GATE - NORTH ON CONCRETE HAUL RD TO NORTH PARKING LOT		
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS -					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER # 26	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK 174
SLUMP 4					

LEAVE PLANT 13:28	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16316 lb	16330 lb	0.08%	0.10% M	2	gl	
SANDFAA	1332 lb	13695 lb	13720 lb	0.18%	2.82% A	45	gl	
CEMENT	450 lb	4500 lb	4500 lb	0.00%				
SLAG	150 lb	1500 lb	1510 lb	0.67%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.20 oz #	42.00 oz	42.00 oz	0.00%				
WATER	30.9 gl	242.1 gl	243.0 gl	0.39%		243.0	gl	-2.00 gl

Num Batches: 1 Manual 13:21:24

Design W/C: 0.430 Water/Cement: 0.429 T Design 309.0 gl Actual 290.0 gl To Add: 19.0 gl

Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYE



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 03/26/2014	ACCOUNT BLISS	TRUCK 0133	DRIVER NAME LANCE DAY	TICKET # 1092901		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH TO SIDEWALK ON EAST SIDE OF GEORGE WILLIAMS WAY				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS -							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER # 9	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK 194	SLUMP 4	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	160	120		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	12		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16318 lb	16320 lb	0.02%	0.10% M	2	gl	
SANDFAA	1332 lb	13710 lb	13750 lb	0.29%	2.93% A	47	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.00 oz #	40.00 oz	39.00 oz	-2.50%				
WATER	30.9 gl	240.3 gl	240.0 gl	-0.12%		240.0	gl	-2.00 gl

Num Batches: 1 Manual 14:28:12

id 38104 lb Design W/C: 0.430 Water/Cement: 0.429 T Design 309.0 gl Actual 288.9 gl To Add: 20.1 gl

mp: 4.00 in Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	03/26/2014	BLISS	0195	Marty Trumble	1092895		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST HAND CURB INTHE PARKING LOT ON RIGHT AT NORTH END OF LOT (SUNFLOWER)				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
53	TEC# 000003471 8	ROCKCHALKPAR		HANDCURB	139	3	
30,412							
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	24	16		
8.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER L	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X _____
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKG MKC	1630 lb	13053 lb	13070 lb	0.13%	0.10% M	2	gl	
SANDFAA	1332 lb	10967 lb	10980 lb	0.12%	2.92% A	37	gl	
CEMENT	450 lb	3600 lb	3605 lb	0.14%				
SLAG	150 lb	1200 lb	1205 lb	0.42%				
WREDUCE1	30.00 oz	240.00 oz	238.00 oz	-0.83%				
AIR1	4.00 oz #	32.00 oz	32.00 oz	0.00%				
WATER	30.9 gl	184.4 gl	184.0 gl	-0.19%		184.0	gl	-3.00 gl

Num Batches: 1

Design 247.2 gl Act 222.9 gl To Add: 24.3 gl

Water/Cement 0.429 T Trim Water: -3.00 gl / CYC

Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/27/2014	BLISS	0139	Kevin Tolbert	1092915
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ON FIRST CONCRETE ROAD BY JOB TRAILER TO JOB		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
47	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	184	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	60	30		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	3		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

11:35 AM
6"
8.0"
90"
SIDEWALK
SUBTOTAL N. SIDE
TAX OFF ROCKCHALKPAR
TOTAL

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

CUSTOMER SIGNATURE X _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16349 lb	16390 lb	0.25%	0.30% M	6	gl	
SANDFAA	1332 lb	13701 lb	13700 lb	-0.01%	2.86% A	46	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1540 lb	+ 2.67%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER	30.9 gl	237.5 gl	237.0 gl	-0.20%		237.0	gl	-2.00 gl

Num Batches: 1
Manual 10:37:02
Design W/C: 0.430 Water/Cement 0.426 T Design 309.0 gl Actual 288.5 gl To Add: 20.5 gl
Water in Truck: 0.0 gl Must Water: 0.0 gl / Load Trim Water: -2.00 / CYE



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/28/2014	BLISS	0152	BRYAN REEVES	1092962
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST SIDE OF PARKINGLOT JUST NORTH OF JOB TRAILER		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
56	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	194	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	80	20		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	2		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

1:11pm
6"
8-5"
47°
S. OF PARKINGLOT
APR 5- POND #1

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wet	Trim
ROCKGMKC	1630 lb	16365 lb	16380 lb	0.09%	0.40% M	8	gl	
SANDFAA	1332 lb	13680 lb	13680 lb	0.00%	2.70% A	43	gl	
CEMENT	450 lb	4500 lb	4525 lb	0.56%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.00 oz #	40.00 oz	39.00 oz	-2.50%				
WATER	30.9 gl	238.1 gl	238.0 gl	-0.04%		238.0	gl	-2.00 gl

Num Batches: 1
Manual 12:30:48
Design W/C: 0.430 Water/Cement: 0.428 T Design 309.0 gl Actual 288.9 gl To Add: 20.1 gl
Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.00 / CYT



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/28/2014	BLISS	0194	CHRISTOPHER DIEH	1092984

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - POURING IN PARKING LOT JUST NORTH OF JOB TRAILER- LUIS' CREW
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	



38,126

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
108	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	113	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	40	40		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	4		
10.00	oz	DARASET	DARASET .50% NON-CHLOF	1	1920		
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

Handwritten notes:
500
9.6"
7.0"
48/10

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

_____ X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME TITLE

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16365 lb	16370 lb	0.03%	0.40% M	8	gl	
SANDFAA	1332 lb	13741 lb	13770 lb	0.21%	3.16% A	51	gl	
CEMENT	450 lb	4500 lb	4500 lb	0.00%				
SLAG	150 lb	1500 lb	1515 lb	1.00%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER	30.9 gl	230.7 gl	230.0 gl	-0.29%		230.0	gl	-2.00 gl
DARASET	48.00 oz	480.00 oz	480.00 oz	0.00%				



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/29/2014	BLISS	0113	TRAVIS MOONEY	1092996
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ON FIRST CONCRETE ROAD BY JOB TRAILER TO JOB		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
24	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	195	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	30	20		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	2		
10.00	ea	SATDC	SATURDAY DELIVERY CHAF	0			
10.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

*10:45 AM
5 3/4"
8.9%
690
DAMPS TO SIDE WALK IN PLOT
SUBTOTAL
TAX
TOTAL*

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16333 lb	16340 lb	0.05%	0.20% M	4	gl	
SANDFAA	1332 lb	13667 lb	13720 lb	0.39%	2.61% A	42	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER	30.9 gl	243.5 gl	243.0 gl	-0.20%		243.0	gl	-2.00 gl



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/31/2014	BLISS	0194	Wayne Grammer	1093035

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - SOUTH ON HAUL RD - WEST ON NEW CONCRETE PATH JUST SOUTH OF SOCCER FIELD
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	



34,472

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
51	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK		4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
9.00	yd	AS6425G4	KCMMB 4K 25% .44	27	9		
9.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	1		
9.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____
X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

J. Kpm

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMC	1830 lb	14743 lb	14750 lb	0.05%	0.50% M	9	gl	
SANDFAA	1332 lb	12276 lb	12450 lb	+ 1.41%	2.41% A	35	gl	
CEMENT	450 lb	4050 lb	4070 lb	0.49%				
SLAG	150 lb	1350 lb	1380 lb	+ 2.22%				
WREDUCE1	30.00 oz	270.00 oz	270.00 oz	0.00%				
AIR1	4.00 oz #	36.00 oz	36.00 oz	0.00%				
WATER	30.9 gl	216.7 gl	216.0 gl	-0.34%		216.0	gl	-2.00 gl

Num Batches: 1
Manual 13:16:40
Design 278.1 gl Act 259.8 gl To Add: 18.3 gl
Water/Cement 0.426 T Trim Water: -2.0 / CYL
Water in Truck: 0.0 gl / Load



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	03/31/2014	BLISS	0113	TRAVIS MOONEY	1093042
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - SOUTH ON HAUL RD TO CASEY'S CREW (SUNFLOWER)		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
76	TEC# 000003471 8	ROCKCHALKPAR		C&G	174	3

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	26	26		
8.00	/y	WINTER	WINTER SERVICE	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

PRINTED NAME

TITLE

X

CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	13105 lb	13120 lb	0.11%	0.50% M	8	gl	
SANDFAA	1332 lb	10906 lb	10920 lb	0.13%	2.35% A	30	gl	
CEMENT	450 lb	3600 lb	3605 lb	0.14%				
SLAG	150 lb	1200 lb	1210 lb	0.83%				
WREDUCE1	30.00 oz	240.00 oz	240.00 oz	0.00%				
AIR1	4.00 oz #	32.00 oz	32.00 oz	0.00%				
WATER	30.9 gl	185.4 gl	185.0 gl	-0.24%		185.0	gl	-3.00 gl

ual Num Batches: 1 Manual 14:29:33
 id 30416 lb Design W/C: 0.430 Water/Cement 0.428 T Design 247.2 gl Act 222.8 gl To Add: 24.4 gl
 mp: 3.00 in # Water in Truck: 0.0 gl just Water: 0.0 gl / Load Trim Water: -3.00 / CYC



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute
Certifications



Certifications

KANSAS
Certifications

PLANT 01	DATE 04/01/2014	ACCOUNT BLISS	TRUCK 0184	DRIVER NAME Shawn Cool	TICKET # 1093096
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - TURN NORTH INTO PARKING LOT		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER # 71	PO# TEC# 000003471	PROJECT CODE ROCKCHALKPAR	JOB# 19,005	APPLICATION HANDCURB	PREVIOUS TRUCK 152	SLUMP 3
---------------	--------------------------	------------------------------	----------------	-------------------------	-----------------------	------------

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.00	yd	AS6425G4	KCMMB 4K 25% .44	15	15		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 5:17	ARRIVE JOB 6:01	START UNLOAD 6:58	FINISH UNLOAD 7:19
LEAVE JOB 7:00	ARRIVE PLANT 7:17	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: gal yds gal yds gal yds gal			

SUBTOTAL	
TAX	
TOTAL	



CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C136. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME: _____ TITLE: _____ CUSTOMER SIGNATURE: _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wet	Trm
ROCKGMKC	1630 lb	8199 lb	8200 lb	0.01%	0.60% M	6	gl	
SANDFAA	1332 lb	6790 lb	6800 lb	0.15%	1.95% A	16	gl	
CEMENT	450 lb	2250 lb	2260 lb	0.44%				
SLAG	150 lb	750 lb	750 lb	0.00%				
WREDUCE1	30.00 oz	150.00 oz	151.00 oz	0.67%				
AIR1	3.80 oz #	19.00 oz	20.00 oz	5.26%				
WATER	30.9 gl	118.1 gl	118.0 gl	-0.06%		118.0	gl	-3.00 gl

ual	Num Batches	1	Manual	17 42 05
id	19005 lb Design W/C	0.430	Water/Cement	0.428 T Design 154.5 gl Actual 139.5 gl To Add 15.1 gl
mp	3.00 in # Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load Trm Water -3.0 gl / CYC



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	04/01/2014	BLISS	0125	STUART BOYLES	1093071
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST ON FIRST CONCRETE RD TOWARDS 902 RD TO CASEY'S CREW(SUNFLOWER)		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

38,144

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
72	TEC# 000003471 8	ROCKCHALKPAR		SIDEWALK	151	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	70	70		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	7		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 10 gal 32 yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mortar gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.


DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C84 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY

X 

CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME TITLE

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	18398 lb	16410 lb	0.07%	0.60% M	12	gl	
SANFAA	1332 lb	13598 lb	13670 lb	0.53%	2.09% A	34	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%				
AIR1	3.80 oz #	38.00 oz	38.00 oz	0.00%				
WATER	30.9 gl	243.9 gl	243.0 gl	-0.38%		243.0	gl	-2.00 gl

Num Batches	1	Manual	14 30 07
Design W/C	0.430	Water/Cement	0.429 T
Design	309.0 gl	Actual	288.3 gl
Adjust Water	0.0 gl / Load	Trim Water	-2.0 gl /
Water in Truck	0.0 gl	CYC	
To Add	20.7 gl		



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
CERTIFICATION

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 04/01/2014	ACCOUNT BLISS	TRUCK 0152	DRIVER NAME BRYAN REEVES	TICKET # 1093064
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH - WEST ONTO DIRT RAMP BETWEEN SOCCER AND SOFTBALL FIELDS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER # 115	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK	SLUMP 4
----------------	-------------------------------	------------------------------	------	------------------------	----------------	------------

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	8	8		
8.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	1		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1224	ARRIVE JOB 1248	START UNLOAD 1249	FINISH UNLOAD 1330
LEAVE JOB 1346	ARRIVE PLANT 1405	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

SUBTOTAL	
TAX	
TOTAL	

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense

PRODUCT PERFORMANCE All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump ASTM C143; Temperature: ASTM C1064; density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.
MSDS and Lion Law information on reverse side

RECEIVED IN GOOD CONDITION BY

Bliss
PRINTED NAME

[Signature]
CUSTOMER SIGNATURE

TITLE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	13118 lb	13120 lb	0.01%	0.60% M	9	gl	
SANDFAA	1332 lb	10680 lb	10920 lb	0.37%	2.10% A	27	gl	
CEMENT	450 lb	3600 lb	3610 lb	0.28%				
SLAG	150 lb	1200 lb	1210 lb	0.83%				
WREDUCE1	30.00 oz	240.00 oz	241.00 oz	0.42%				
AIR1	3.50 oz #	28.00 oz	28.00 oz	0.00%				
WATER	30.9 gl	195.0 gl	195.0 gl	-0.02%		195.0	gl	-2.00 gl

Num Batches: 1

Manual 12:18:18

Design W/C: 0.430 Water/Cement: 0.428 T Design 247.2 gl Actual 231.3 gl To Add: 15.9 gl

mp: 4.00 in Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CY



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	04/01/2014	BLISS	0115	GLYNN TIPTON	1093089
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TWEST ON FIRST CONCRETERD TOWARDS 902 RD TO LUIS' CREW(SUNFLOWER)		
			NOTE:		
			20,958		
			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
141	TEC# 000003471	ROCKCHALKPAR		RAMP		4
	8					

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.50	yd	AS6425G4	KCMMB 4K 25% .44	5.5	5.5		
5.50	/y	FIBERS	GRACE POLYPROPYLENE FI	1	1		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	1643	ARRIVE JOB	1703	START UNLOAD	1714	FINISH UNLOAD	1750
LEAVE JOB	1809	ARRIVE PLANT		TEST CYLINDERS TAKEN	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO	
				BEFORE H2O ADDED	<input type="checkbox"/> YES	<input checked="" type="checkbox"/> NO	

SUBTOTAL	
TAX	
TOTAL	

PURCHASER OF THIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal NA

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature: ASTM C1064, density and/or yield: ASTM C138. Slump and air-entrainment: variances in accordance to ASTM C84 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Bliss Sports

PRINTED NAME: _____ TITLE: _____

CUSTOMER SIGNATURE: _____
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Tnm
ROCKGMKC	1630 lb	9019 lb	9040 lb	0.24%	0.60% M	6	gl	
SANDFAA	1332 lb	7472 lb	7470 lb	-0.03%	1.99% A	17	gl	
CEMENT	450 lb	2475 lb	2480 lb	0.20%				
SLAG	150 lb	825 lb	830 lb	0.61%				
WREDUCE1	30.00 oz	165.00 oz	165.00 oz	0.00%				
AIR1	3.80 oz #	20.90 oz	20.00 oz	-4.31%				
WATER	30.9 gl	135.0 gl	135.0 gl	0.00%		135.0	gl	-2.00 gl

Num Batches	1	Manual	16 32 35
20958 lb	Design W/C 0.430	Water/Cement 0.429	T Design 170.0 gl
4.00 in	Water in Truck 0.0 gl	Adjust Water 0.0 gl / Load	Tnm Water -2.0 gl /
			Actual 159.0 gl To Add 11.0 gl
			CYC



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
CERTIFICATIONS

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	04/04/2014	BLISS	0137	BRIAN LINDELOF	1093140

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - WEST ON DIRT SOUTH OF SOCCER FIELD TO JOB - JOB IS EAST OFFIELDS
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	



11,280

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
39	TEC# 000003471	ROCKCHALKPAR		HANDPAV	184	3
8						

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
3.00	CYDS	AS6525G4	KCMMB 5K 25% .40	73	73		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT <i>16:57</i>	ARRIVE JOB <i>16:56</i>	START UNLOAD <i>16:32</i>	FINISH UNLOAD <i>17:02</i>
LEAVE JOB <i>17:16</i>	ARRIVE PLANT <i>17:33</i>	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME

TITLE

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trm
SANFFAA	1297 lb	3984 lb	3990 lb	0.14%	2.40% A	11	gl	
ROCKGMKC	1586 lb	4801 lb	4810 lb	0.19%	0.90% M	5	gl	
CEMENT	495 lb	1485 lb	1485 lb	0.00%				
SLAG	165 lb	495 lb	495 lb	0.00%				
AIR1	5.00 oz #	15.00 oz	15.00 oz	0.00%				
WREDUCE1	35.25 oz	105.75 oz	106.00 oz	0.24%				
WATER	317 gl	72.8 gl	59.0 gl	-18.95%		59.0	gl	-2.00 gl

ual		Num Batches	1			Manual	16 03 31			
id	11280 lb	Design W/C	0.401	T	Design	95.1 gl	Actual	75.3 gl	To Add	19.8 gl
mp	3.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trm Water	-2.0 gl /	CYC		



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute*
Certifications



Certifications



PLANT 01	DATE 04/04/2014	ACCOUNT BLISS	TRUCK 0149	DRIVER NAME KEVIN BLACK	TICKET # 1093131
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH TO PUMP		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

19,022

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
45	TEC# 000003471	ROCKCHALKPAR		RAMP	146	4

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.00	CYDS	AS6525G4	KCMMB 5K 25% .40	215	175		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT B17	ARRIVE JOB 137	START UNLOAD 140	FINISH UNLOAD 159
LEAVE JOB 1513	ARRIVE PLANT 1531	TEST CYLINDERS TAKEN BEFORE H2O ADDED	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>
PURCHASER OF THIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal			

SUBTOTAL

TAX

TOTAL

GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and/or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law Information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME: BLISS (BB PUMP) TITLE: C.M.

CUSTOMER SIGNATURE: X (BLISS)

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trm
SANDFAA	1297 lb	6638 lb	6680 lb	0.63%	2.36% A	18	gl	
ROCKGMKC	1588 lb	8001 lb	8010 lb	0.11%	0.90% M	9	gl	
CEMENT	495 lb	2475 lb	2480 lb	0.20%				
SLAG	165 lb	825 lb	830 lb	0.61%				
AIR1	5.00 oz #	25.00 oz	25.00 oz	0.00%				
WREDUCE1	35.25 oz	176.25 oz	176.00 oz	-0.14%				
WATER	31.7 gl	121.6 gl	121.0 gl	-0.47%		121.0	gl	-2.00 gl

ua	Num Batches	1	Manual	13 11 56
id	19022 lb Design W/C	0.401	Water/Cement	0.400 T
mp	4.00 in # Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load
			Design	158.5 gl
			Actual	148.1 gl
			To Add	10.4 gl
			Trm Water	-2.0 gl /
			CYC	



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
Cement and Concrete
Certifications

PLANT 01	DATE 04/05/2014	ACCOUNT BLISS	TRUCK 0184	DRIVER NAME Shawn Cool	TICKET # 1093142
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - POURING ON THE FAR SOUTH END OF THE TRACK		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

38,001

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
14	TEC# 000003471 8	ROCKCHALKPAR		APPROACH	194	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	CYDS	AS6525G4	KCMMB 5K 25% .40	20	20		
10.00	ea	SATDC	SATURDAY DELIVERY CHAF	0			
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 813	ARRIVE JOB 832	START UNLOAD 872	FINISH UNLOAD 855
LEAVE JOB 909	ARRIVE PLANT 929	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY

Buddy
PRINTED NAME

Jimman
TITLE

X Buddy
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Tnm
SANDFAA	1297 lb	13337 lb	13350 lb	0.10%	2.83% A	44	gl	
ROCKGMKC	1586 lb	15987 lb	16000 lb	0.08%	0.80% M	15	gl	
CEMENT	495 lb	4950 lb	4985 lb	0.71%				
SLAG	165 lb	1650 lb	1655 lb	0.30%				
AIR1	5.00 oz #	50.00 oz	50.00 oz	0.00%				
WREDUCE1	35.25 oz	352.50 oz	353.00 oz	0.14%				
WATER	31.7 gl	237.9 gl	238.0 gl	0.06%		238.0	gl	-2.00 gl

ual	Num Batches	1	Manual	8 07 30							
id	38001 lb	Design W/C	0.401	Water/Cement	0.398 T	Design	317.0 gl	Actual	297.2 gl	To Add	19.8 gl
mp	4.00 in #	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Tnm Water	-2.0 gl /	CYC			



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF THE AGRICULTURE
Certifications

PLANT 01	DATE 04/07/2014	ACCOUNT BLISS	TRUCK 0159	DRIVER NAME Kevin Tolbert	TICKET # 1093147		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - POURING ON THE FAR SOUTH END OF THE TRACK				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER # 68	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION EXTFW	PREVIOUS TRUCK 174		
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	CYDS	AS6525G4	KCMMB 5K 25% .40	30	30		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 8:55	ARRIVE JOB 9:10	START UNLOAD 9:35	FINISH UNLOAD 10:15
LEAVE JOB 10:35	ARRIVE PLANT 10:45	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal			

SUBTOTAL

TAX

TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways and other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards: Compressive strength ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature: ASTM C1064, density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY

PRINTED NAME

Casey

TITLE

X

CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trm
SANDFAA	1297 lb	13342 lb	13350 lb	0.06%	2.87% A	45	gl	
ROCKGMKC	1586 lb	16019 lb	16040 lb	0.13%	1.00% M	19	gl	
CEMENT	495 lb	4950 lb	5030 lb	+ 1.62%				
SLAG	165 lb	1650 lb	1665 lb	0.91%				
AIR1	5.00 oz #	50.00 oz	49.00 oz	-2.00%				
WREDUCE1	35.25 oz	352.50 oz	352.00 oz	-0.14%				
WATER	31.7 gl	233.4 gl	233.0 gl	-0.18%		233.0	gl	-2.00 gl

ual Num Batches 1 Manual 8 51 44
 id 38054 lb Design W/C 0.401 Water/Cement 0.395 T Design 317.0 gl Actual 296.6 gl To Add 20.4 gl
 mp 4.00 in # Water in Truck 0.0 gl Adjust Water 0.0 gl / Load Trm Water -2.0 gl / CYC



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



MADOT
Certifications

KANSAS
CERTIFICATION OF CONCRETE
CERTIFICATIONS

PLANT 01	DATE 04/07/2014	ACCOUNT BLISS	TRUCK 0174	DRIVER NAME DOUG BERG	TICKET # 1093167
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH TO CASEY'S CREW (SUNFLOWER)		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER # 54	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB# 34,246	APPLICATION HANDCURB	PREVIOUS TRUCK SLUMP 3

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
9.00	yd	AS6425G4	KCMMB 4K 25% .44	30	9		
150.00	ea	EXPJT6	6" REGULAR EXPANSION J	150	150		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1102	ARRIVE JOB 1222	START UNLOAD 1232	FINISH UNLOAD 1321
LEAVE JOB 1340	ARRIVE PLANT 1402	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and/or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey
PRINTED NAME

Assoc
TITLE

X Casey
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	14817 lb	14840 lb	0.16%	1.00% M	18	gl	
SANDFAA	1332 lb	12306 lb	12350 lb	0.36%	2.65% A	38	gl	
CEMENT	450 lb	4050 lb	4060 lb	0.25%				
SLAG	150 lb	1350 lb	1350 lb	0.00%				
WREDUCE1	30.00 oz	270.00 oz	270.00 oz	0.00%				
AIR1	4.00 oz #	36.00 oz	37.00 oz	2.78%				
WATER	30.9 gl	195.5 gl	195.0 gl	-0.24%		195.0	gl	-3.00 gl

Num Batches 1

Manual 11 52 29

Actual 250.8 gl To Add 27.3 gl

Design 278.1 gl

Water/Cement 0.430

Adjust Water 0.0 gl / Load

Trim Water -3.0 gl / CYL



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 04/07/2014	ACCOUNT BLISS	TRUCK 0113	DRIVER NAME TRAVIS MOONEY	TICKET # 1093163
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD SOUTH - POURING ON THE FAR SOUTH END OF THE TRACK		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

32,357

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
80	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	137	4

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.50	yd	AS6425G4	KCMMB 4K 25% .44	17	17		
8.50	/y	FIBERS	GRACE POLYPROPYLENE FI	1	2		
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1136	ARRIVE JOB 1156	START UNLOAD 1216	FINISH UNLOAD 1311
LEAVE JOB 1327	ARRIVE PLANT 1345	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal 20 yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

GRAND TOTAL

RECEIVED IN GOOD CONDITION BY

PRINTED NAME

TITLE

X

CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	13994 lb	14000 lb	0.05%	1.00% M	17	gl	
SANDFAA	1332 lb	11590 lb	11590 lb	0.00%	2.37% A	32	gl	
CEMENT	450 lb	3825 lb	3825 lb	0.00%				
SLAG	150 lb	1275 lb	1280 lb	0.39%				
WREDUCE1	30.00 oz	255.00 oz	255.00 oz	0.00%				
AIR1	4.00 oz #	34.00 oz	33.00 oz	-2.94%				
WATER	30.9 gl	198.9 gl	197.0 gl	0.06%		197.0	gl	-2.00 gl

ual Num Batches 1 Manual 11 28 51
id 32357 lb Design W/C 0.430 Water/Cement 0.429 T Design 252.7 gl Actual 245.8 gl To Add 16.9 gl
mp 4.00 in Water in Truck 0.0 gl Adjust Water 0.0 gl / Load Trim Water -2.0 gl / CYL



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
CERTIFICATIONS

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 04/07/2014	ACCOUNT BLISS	TRUCK 0123	DRIVER NAME TIMOTHY BELTON	TICKET # 1093183
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TOTHE CORNER WHERE THEJOB TRAILER USED TO BE		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER # 93	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB# 38,089	APPLICATION	PREVIOUS TRUCK 133 SLUMP 4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	30	30		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	3		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 341	ARRIVE JOB 401	START UNLOAD 425	FINISH UNLOAD 520
LEAVE JOB 535	ARRIVE PLANT 717	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Eten Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X  CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual Wat	Trim
ROCKGMKC	1630 lb	16463 lb	16500 lb	0.22%	1.00% M	20 gl	
SANDFAA	1332 lb	13614 lb	13610 lb	-0.03%	2.21% A	35 gl	
CEMENT	450 lb	4500 lb	4505 lb	0.11%			
SLAG	150 lb	1500 lb	1500 lb	0.00%			
WREDUCE1	30.00 oz	300.00 oz	300.00 oz	0.00%			
AIR1	4.00 oz #	40.00 oz	41.00 oz	2.50%			
WATER	30.9 gl	234.2 gl	234.0 gl	-0.09%		234.0 gl	-2.00 gl

ual id mp 38089 lb 4.00 in

Num Batches 1

Design W/C 0.430

Water in Truck 0.0 gl

Water/Cement 0.429 T

Adjust Water

Design 309.0 gl

0.0 gl / Load

Manual 15.32 08

Actual 288.8 gl

To Add 20.2 gl

CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications



PLANT 01	DATE 04/07/2014	ACCOUNT BLISS	TRUCK 0159	DRIVER NAME Kevin Tolbert	TICKET # 1093188
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH TO JOB - SIDEWALK		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

38,081

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
107	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	113	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	20	20		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	2		
1.00	ea	FUELVN	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 7:00	ARRIVE JOB 7:20	START UNLOAD 7:30	FINISH UNLOAD 7:55
LEAVE JOB 5:20	ARRIVE PLANT 5:40	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and/or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME: _____ TITLE: _____

CUSTOMER SIGNATURE: X _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
ROCKGMKC	1630 lb	16463 lb	16480 lb	0.10%	1.00% M	20	gl	
SANDFAA	1332 lb	13676 lb	13670 lb	-0.05%	2.68% A	43	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1505 lb	0.33%				
WREDUCE1	30.00 oz	300.00 oz	299.00 oz	-0.33%				
AIR1	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER	30.9 gl	226.8 gl	227.0 gl	0.11%		227.0	gl	-2.00 gl

ual Num Batches 1 Manual 15 56 07
 id 38081 lb Design W/C 0.430 Water/Cement 0.429 T Design 309.0 gl Actual 289.2 gl To Add 19.8 gl
 mp 4.00 in Water in Truck 0.0 gl Adjust Water 0.0 gl / Load Trim Water -2.0 gl / CYC



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Kansas
Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 04/08/2014	ACCOUNT BLISS	TRUCK 0137	DRIVER NAME BRIAN LINDELOF	TICKET # 1093210
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST AT FIRST CONCRETE RD TO INTERSECTION WITH HAUL RD		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER # 83	PO# TEC# 000003471	PROJECT CODE ROCKCHALKPAR	JOB# 38,092	APPLICATION SIDEWLK	PREVIOUS TRUCK 184 SLUMP 4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	56	56		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	6		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1337	ARRIVE JOB 1355	START UNLOAD 1400	FINISH UNLOAD 1443
LEAVE JOB# 1452	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires lowering, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature: ASTM C1064, density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

CUSTOMER SIGNATURE: *[Signature]*
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trm
ROCKGMKC	1630 lb	16447 lb	16480 lb	0.20%	0.90% M	18	gl	
SANDFAA	1332 lb	13725 lb	13720 lb	-0.04%	3.04% A	49	gl	
CEMENT	450 lb	4500 lb	4510 lb	0.22%				
SLAG	150 lb	1500 lb	1500 lb	0.00%				
WREDUCE1	30 00 oz	300 00 oz	300 00 oz	0.00%				
AIR1	4 00 oz #	40 00 oz	40 00 oz	0.00%				
WATER	30 9 gl	222 9 gl	223 0 gl	0.05%		223 0	gl	-2 00 gl

Manual 13 28 33
Actual 289 1 gl To Add 19 9 gl
Design 309 0 gl
Water/Cement 0 429 T
Adjust Water 0 0 gl / Load Trm Water -2 0 gl / CYC
Design W/C 0 430
Water in Truck 0 0 gl



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
MEMBER OF THE PROFESSION
Certifications

PLANT 01	DATE 04/09/2014	ACCOUNT BLISS	TRUCK 0108	DRIVER NAME SHAD HORCHEM	TICKET # 1093244		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST AT FIRST CONCRETE RD- HAUL RD NORTH TO END - GOWEST TO NORTH END OF TRACK - PAVING				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER # 65	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB# 30,372	APPLICATION	PREVIOUS TRUCK 152 SLUMP 3		
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	CYDS	AS6525G4	KCMMB 5K 25% .40	50	47		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1554	ARRIVE JOB 1614	START UNLOAD 1626	FINISH UNLOAD 1708
LEAVE JOB 1718	ARRIVE PLANT 1911	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature: ASTM C1064, density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept delivery of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Sunflower

PRINTED NAME: _____ TITLE: _____

X CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
SANDFAA	1297 lb	10609 lb	10610 lb	0.01%	2.25% A	28	gl	
ROCKGMKC	1586 lb	12802 lb	12820 lb	0.14%	0.90% M	14	gl	
CEMENT	495 lb	3960 lb	3975 lb	0.38%				
SLAG	165 lb	1320 lb	1320 lb	0.00%				
AIR1	5.00 oz #	40.00 oz	40.00 oz	0.00%				
WREDUCE1	35.25 oz	282.00 oz	280.00 oz	-0.71%				
WATER	31.7 gl	195.9 gl	195.0 gl	-0.48%		195.0	gl	-2.00 gl

ua/	Num Batches	1	Manual	15.44	30
rd	30372 lb	Design W/C	0.401	Water/Cement	0.400 T
mp	3.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load
		Design	253.6 gl	Actual	236.7 gl
		Trim Water	-2.0 gl /	CYL	
		To Add	16.9 gl		



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
CERTIFICATIONS

PLANT 01	DATE 04/09/2014	ACCOUNT BLISS	TRUCK 0174	DRIVER NAME Kevin Tolbert	TICKET # 1093220
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - WEST AT FIRST CONCRETE RD TO INTERSECTION WITH HAUL RD		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

17,154

ORDER # 79	PO# TEC# 000003471	PROJECT CODE ROCKCHALKPAR	JOB# 8	APPLICATION SIDEWLK	PREVIOUS TRUCK	SLUMP 4
---------------	--------------------------	------------------------------	-----------	------------------------	----------------	------------

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
4.50	yd	AS6425G4	KCMMB 4K 25% .44	4.5	4.5		
4.50	/y	FIBERS	GRACE POLYPROPYLENE FI	1	1		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 7:37	ARRIVE JOB 7:58	START UNLOAD 8:10	FINISH UNLOAD 8:59
LEAVE JOB 9:12	ARRIVE PLANT 9:32	TEST CYLINDERS TAKEN BEFORE H2O ADDED YES NO	YES NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey
PRINTED NAME

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Tnm
ROCKGMKC	1630 lb	7401 lb	7420 lb	0.26%	0.90% M	8	gl	
SANDFAA	1332 lb	6127 lb	6140 lb	0.21%	2.22% A	16	gl	
CEMENT	450 lb	2025 lb	2025 lb	0.00%				
SLAG	150 lb	675 lb	675 lb	0.00%				
WREDUCE1	30.00 oz	135.00 oz	134.00 oz	-0.74%				
AIR1	4.00 oz #	18.00 oz	18.00 oz	0.00%				
WATER	30.9 gl	106.2 gl	106.0 gl	-0.18%		106.0	gl	-2.00 gl

ual	Num Batches	1	Manual	7 34 45								
id	17154 lb	Design W/C	0.430	Water/Cement	0.430	T	Design	139.1 gl	Actual	129.9 gl	To Add	9.1 gl
mp	4.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Tnm Water	-2.0 gl /	CYL				



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	04/10/2014	BLISS	0113	TRAVIS MOONEY	1093258
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - FIRST CONCRETE RD WEST - NORTH ON HALL RD TO END - WEST TO NORTH END OF SOFTBALL FIELD - PAVING (SUNFLOWER)		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

7,599

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
87	TEC# 000003471	ROCKCHALKPAR		APPROACH	194	4
	8					

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
2.00	CYDS	AS6525G4	KCMMB 5K 25% .40	22	22		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1122	ARRIVE JOB 1138	START UNLOAD 1143	FINISH UNLOAD 1152
LEAVE JOB 1205	ARRIVE PLANT 1225	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and/or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Trim
SANDFAA	1297 lb	2653 lb	2660 lb	0.26%	2.28% A	7	gl	
ROCKGMKC	1586 lb	3201 lb	3210 lb	0.30%	0.90% M	3	gl	
CEMENT	495 lb	990 lb	1005 lb	1.52%				
SLAG	165 lb	330 lb	335 lb	1.52%				
AIR1	5.00 oz #	10.00 oz	9.00 oz	-10.00%				
WREDUCE1	35.25 oz	70.50 oz	71.00 oz	0.71%				
WATER	31.7 gl	46.9 gl	46.0 gl	-1.88%		46.0	gl	-3.00 gl

ua	Num Batches	1	Manual	11 18 53					
id	7599 lb Design W/C	0.401	Water/Cement	0.395 T Design	63.4 gl	Actual	56.5 gl	To Add	6.9 gl
mp	4.00 in # Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water	-3.0 gl /	CY		



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	04/10/2014	BLISS	0113	TRAVIS MOONEY	1093262
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - FIRST CONCRETE RD WEST - NORTH ON HALL RD TO END - WEST TO NORTH END OF SOFTBALL FIELD - SIDEWALK (SUNFLOWER)		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

31,408

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
129	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	194	4

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.25	yd	AS6425G4	KCMMB 4K 25% .44	16.5	16.5		
8.25	/y	FIBERS	GRACE POLYPROPYLENE FI	1	2		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1241	ARRIVE JOB 1300	START UNLOAD 1331	FINISH UNLOAD 1347
LEAVE JOB 1359	ARRIVE PLANT 1416	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 8 gal 10 yds 8 gal 10 yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSOS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature: ASTM C1064, density and or yield: ASTM C139. Slump and air entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSOS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Design Qty	Required	Batched	% Var	% Moisture	Actual	Wat	Tnm
ROCKMKC	1830 lb	13569 lb	13570 lb	0.01%	0.90% M	15	gl	
SANDFAA	1332 lb	11243 lb	11240 lb	-0.03%	2.31% A	30	gl	
CEMENT	450 lb	3713 lb	3725 lb	0.34%				
SLAG	150 lb	1238 lb	1245 lb	0.61%				
WREDUCE1	30.00 oz	247.50 oz	246.00 oz	-0.61%				
AIR1	4.00 oz #	33.00 oz	32.00 oz	-3.03%				
WATER	30.9 gl	193.5 gl	193.0 gl	-0.24%		193.0	gl	-2.00 gl

ual	Num Batches	1	Manual	12 35 33								
id	31408 lb	Design W/C	0.430	Water/Cement	0.428	T	Design	254.9 gl	Actual	237.9 gl	To Add	17.0 gl
mp	4.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Tnm Water	-2.0 gl /	CYT				



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
 SHAWNEE MISSION, KANSAS 66227-2705
 DISPATCH (913) 441-4197 OFFICE (913) 441-8781
 (800) 322-9710 (800) 524-6474



American Concrete Institute
 Certifications



Certifications



KANSAS
 CERTIFICATION OF THE PROFESSION
 Certifications

www.pennysconcrete.com
 An Equal Opportunity Employer

PLANT 01	DATE 04/16/2014	ACCOUNT BLISS	TRUCK 0112	DRIVER NAME LANCE ATKINS	TICKET # 1093414
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH - FIRST CONCRETE RD WEST - NORTH ON HALL RD TO NORTH PARKING LOT		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
		30,729	NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER # 29	PO# TEC# 000003471	PROJECT CODE ROCKCHALKPAR	JOB# 8	APPLICATION MAINLINE	PREVIOUS TRUCK 149
SLUMP 4					

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	98	98		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1255	ARRIVE JOB 1315	START UNLOAD 1319	FINISH UNLOAD 1337
LEAVE JOB 1355	ARRIVE PLANT 1415	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
 TAX
 TOTAL
 GRAND TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 8 gal 10 yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways and all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173 Slump: ASTM C143 Temperature: ASTM C1064 density and/or yield: ASTM C138 Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey
 PRINTED NAME

Assoc
 TITLE

X Casey
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
lenal	CKGMKC KC APPROVED G	1630 lb	13131 lb	13140 lb	0.07%	0.70% M		11 gl	
NDFAA	PA1 LAWRENCE	1332 lb	10896 lb	10900 lb	0.04%	2.25% A		29 gl	
MENT	BUZZI CG	450 lb	3600 lb	3865 lb	7.36%				
AG	HOLCIM IND	150 lb	1200 lb	1205 lb	0.42%				
REDUCE1	WE GRACE ADV/	30.00 oz	240.00 oz	240.00 oz	0.00%				
tt	WR GRACE DAR/	4.50 oz	36.00 oz	35.00 oz	-2.78%				
ATER	WATER	30.9 gl	191.5 gl	192.0 gl	0.26%			192.0 gl	

Manual	12 46 52
Actual	231 7 gl
To Add	15 5 gl

Num Batches	1
Design W/C	0.430
Water/Cement	0.407 T
Design	247 2 gl
Actual	-2 0 gl /
Adjust Water	0 0 gl / Load
Trm Water	
CYC	



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
 SHAWNEE MISSION, KANSAS 66227-2705
 DISPATCH (913) 441-4197 OFFICE (913) 441-8781
 (800) 322-9710 (800) 524-6474




American Concrete Institute
 Certifications



Certifications

KANSAS
 CONCRETE CERTIFICATIONS

www.pennysconcrete.com
 An Equal Opportunity Employer

PLANT #	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	04/22/2014	BLISS	0194	Wayne Grammer	1093520
CUSTOMER NAME			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
BLISS SPORTS LLC			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH -		
JOB ADDRESS			FIRST CONCRETE RD WEST - HALL RD NORTH TO		
6100 ROCK CHALK DR - ROCK CHALK			NORTH PARKING LOT (SUNFLOWER CREW)		
PARK - LAWRENCE, KS					
			NOTE:		
22,841			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,		
			STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
30	TEC# 000003471 8	ROCKCHALKPAR		HANDCURB	113	4

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
6.00	yd	AS6425G4	KCMMB 4K 25% .44	76	76		
1.00	ea	FUELVN	FUEL SURCHARGE - PER L	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
5:32	6:10	5:00	5:20
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	BEFORE H2O ADDED
6:10	6:10	<input type="checkbox"/> YES	<input type="checkbox"/> YES

SUBTOTAL	
TAX	
TOTAL	
GRAND TOTAL	

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss, or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064 density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Bliss x Bliss

PRINTED NAME TITLE CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Water
CKGMKC	PCI APPROVED G	1630 lb	9858 lb	9880 lb	0.22%	0.80% M		9 gl	
NDFAA	PAI LAWRENCE	1332 lb	8149 lb	8160 lb	0.14%	1.96% A		19 gl	
MENT	BUZZI CG	450 lb	2700 lb	2720 lb	0.74%				
%G	HOLCIM IND	150 lb	900 lb	900 lb	0.00%				
REDUCE1	WE GRACE ADV/	30.00 oz	180.00 oz	180.00 oz	0.00%				
WATER	WR GRACE DAR/	4.20 oz #	25.20 oz	25.00 oz	-0.79%				
		30.9 gl	139.2 gl	140.0 gl	0.57%			140.0 gl	

Manual	16 15 36
Actual	168.2 gl
To Add	17.2 gl
Design	185.4 gl
Water in Truck	0.0 gl
Adjust Water	0.0 gl / Load
Design	185.4 gl / Load
Actual	-3.0 gl / CYC



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

TRUCK #	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/01/2014	BLISS	0139	Kevin Tolbert	1093622		
CUSTOMER NAME			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
BLISS SPORTS LLC			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH				
JOB ADDRESS			TURNS WEST - HALL RD NORTH TO NORTH PARKING				
6100 ROCK CHALK DR - ROCK CHALK			LOT (SUNFLOWER CREW)				
PARK - LAWRENCE, KS							
			NOTE:				
38,074			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,				
			STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
24	TEC#	ROCKCHALKPAR		HANDCURB		3	
000003471							
8							
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	20	10		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
1235	1250	1255	1255
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
140	135	BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. GRAND TOTAL

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casper *ASAC*

PRINTED NAME _____ TITLE _____

X CUSTOMER SIGNATURE _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Serial	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	16479 lb	16520 lb	0.25%	1.10% M		22 gl	
NDFAA	PAI LAWRENCE	1332 lb	13639 lb	13690 lb	0.38%	2.39% A		38 gl	
MENT	BUZZI CG	450 lb	4500 lb	4505 lb	0.11%				
%G	HOLCIM IND	150 lb	1500 lb	1510 lb	0.67%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	301.00 oz	0.33%				
11	WR GRACE DAR/	3.80 oz #	38.00 oz	37.00 oz	-2.63%				
ITER	WATER	30.9 gl	219.3 gl	219.0 gl	-0.15%			219.0 gl	

ual	Num Batches	1	Manual	12.29.34
id	38074 lb Design W/C	0.430	Actual	278.9 gl To Add
mp	3.00 in # Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load Trim Water
			-3.0 gl /	CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PERMIT 01	DATE 05/01/2014	ACCOUNT BLISS	TRUCK 0137	DRIVER NAME BRIAN LINDELOF	TICKET # 1093626
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW)		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
38,047					

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
137	TEC# 000003471 8	ROCKCHALKPAR		MAINLINE	159	4	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	40	40		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 15:00	ARRIVE JOB 15:28	START UNLOAD 15:48	FINISH UNLOAD 16:13
LEAVE JOB 16:30	ARRIVE PLANT 16:54	TEST CYLINDERS TAKEN BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side

RECEIVED IN GOOD CONDITION BY

X Brian Lindelof
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	16512 lb	16550 lb	0.23%	1.30% M		25 gl	
NDFAA	PAI LAWRENCE	1332 lb	13641 lb	13660 lb	0.14%	2.41% A		39 gl	
MENT	BUZZI CG	450 lb	4500 lb	4525 lb	0.56%				
%G	HOLCIM IND	150 lb	1500 lb	1505 lb	0.33%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	299.00 oz	-0.33%				
1	WR GRACE DAR/	4.00 oz #	40.00 oz	40.00 oz	0.00%				
ITER	WATER	30.9 gl	215.1 gl	214.0 gl	-0.51%			214.0 gl	
Manual								15.14	44
Actual								278.0 gl	To Add 31.0 gl
mp	4.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water		-3.0 gl /	CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute*
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PSBT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/02/2014	BLISS	0113	TONY RICHESON	1093637		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW)				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
73	TEC# 000003471	ROCKCHALKPAR		HANDCURB	159	3	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.50	yd	AS6425G4	KCMMB 4K 25% .44	25.5	25.5		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 11:43	ARRIVE JOB 12:02	START UNLOAD 12:11	FINISH UNLOAD 12:53
LEAVE JOB 1:10	ARRIVE PLANT 1:29	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL	
TAX	
TOTAL	

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, nose immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

Bliss

CUSTOMER SIGNATURE: *X Bliss*

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKG MKC	KC APPROVED G	1630 lb	9064 lb	9090 lb	0.29%	1.10% M		12 gl	
NDFAA	PAI LAWRENCE	1332 lb	7503 lb	7520 lb	0.23%	2.41% A		21 gl	
MENT	BUZZI CG	450 lb	2475 lb	2475 lb	0.00%				
AG	HOLCIM IND	150 lb	825 lb	830 lb	0.61%				
REDUCE 1	WE GRACE ADV	30.00 oz	165.00 oz	165.00 oz	0.00%				
TI	WR GRACE DAR	3.80 oz	20.90 oz	21.00 oz	0.48%				
ATER	WATER	30.9 gl	120.5 gl	120.0 gl	-0.38%			120.0 gl	

Manual	11 36 25
Actual	153.1 gl
To Add	18.9 gl
CYT	

Num Batches	1
Design W/C	0.430
Water/Cement	0.429 T
Design	170.0 gl
Actual	170.0 gl
Trm Water	
Adjust Water	0.0 gl / Load
Water in Truck	0.0 gl
Adjust Water	



www.pennysconcrete.com
An Equal Opportunity Employer


PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications



PLANT 01	DATE 05/02/2014	ACCOUNT BLISS	TRUCK 0112	DRIVER NAME LANCE ATKINS	TICKET # 1093654
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW)		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS					
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

30,487

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
75	TEC# 000003471 8	ROCKCHALKPAR		PAVING	159	4

QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	28	28		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1453	ARRIVE JOB 1516	START UNLOAD 1527	FINISH UNLOAD 1544
LEAVE JOB 1610	ARRIVE PLANT 1631	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 8 gal 6 yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. **GRAND TOTAL**

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey
PRINTED NAME

Assoc
TITLE

X Casey
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	13183 lb	13200 lb	0.13%	1.10% M		17 gl	
NDFAA	PAI LAWRENCE	1332 lb	10953 lb	10970 lb	0.15%	2.79% A		36 gl	
MENT	BUZZI CG	450 lb	3600 lb	3610 lb	0.28%				
WG	HOLCIM IND	150 lb	1200 lb	1205 lb	0.42%				
REDUCE1	WE GRACE ADV/	30.00 oz	240.00 oz	240.00 oz	0.00%				
WATER	WR GRACE DAR/	4.00 oz #	32.00 oz	31.00 oz	-3.13%				
		30.9 gl	178.4 gl	178.0 gl	-0.21%			178.0 gl	

Actual	30487 lb	Design W/C	0.430	Water/Cement	0.428 T	Design	247.2 gl	Actual	230.9 gl	Manual	14.4637	To Add	16.3 gl
mp	4.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water	-2.0 gl /	CYT					



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PERMIT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	05/02/2014	BLISS	0122	TRAVIS MOONEY	1093662
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TO PUMP		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

38,116

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
142	TEC# 000003471	ROCKCHALKPAR		SIDEWLK	137	4
	8					

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	80	80		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	8		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1652	ARRIVE JOB 1714	START UNLOAD 1725	FINISH UNLOAD
LEAVE JOB 1755	ARRIVE PLANT 1815	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 10 gal 10 yds 4.5 gal 9 yds 7.5 gal 5 yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mortar gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveway, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C136. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials heretofore sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME _____ TITLE _____
 X
 CUSTOMER SIGNATURE
 NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
enl	CKGMKC KC APPROVED G	1630 lb	16479 lb	16520 lb	0.25%	1.10% M		22 gl	
ndfaa	PAI LAWRENCE	1332 lb	13672 lb	13700 lb	0.21%	2.84% A		42 gl	
ment	BUZZI CG	450 lb	4500 lb	4500 lb	0.00%				
ag	HOLCIM IND	150 lb	1500 lb	1505 lb	0.33%				
reduce1	WE GRACE ADV	30.00 oz	300.00 oz	300.00 oz	0.00%				
11	WR GRACE DAR	4.00 oz #	40.00 oz	40.00 oz	0.00%				
water	WATER	30.9 gal	225.4 gal	224.0 gal	-0.61%			224.0 gl	

total	38116 lb	Design W/C	0.430	Water/Cement	0.429 T	Design	309.0 gl	Actual	287.8 gl	To Add	21.2 gl
mp	4.00 in	Water in Truck	0.0 gal	Adjust Water	0.0 gl / Load	Trim Water	-2.0 gl /	CYL			



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/05/2014	BLISS	0139	Kevin Tolbert	1093694		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW)				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
53	TEC# 000003471 8	ROCKCHALKPAR		HANDCURB	139	3	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	30	14.5		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 2:25	ARRIVE JOB 7:45	START UNLOAD 8:50	FINISH UNLOAD 9:00
LEAVE JOB 4:15	ARRIVE PLANT 4:30	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
PURCHASER/DRIVER AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal			

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK. GRAND TOTAL

DELIVERY AGREEMENT This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173 Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138 Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey Forman X
PRINTED NAME TITLE CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
lenal	KC APPROVED G	1630 lb	16528 lb	16550 lb	0.13%	1.40% M		27 gl	
NDFAA	PAI LAWRENCE	1332 lb	13669 lb	13690 lb	0.16%	2.82% A		42 gl	
MENT	BUZZI CG	450 lb	4500 lb	4500 lb	0.00%				
AG	HOLCIM IND	150 lb	1500 lb	1500 lb	0.00%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	300.00 oz	0.00%				
!1	WR GRACE DAR/	4.50 oz #	45.00 oz	46.00 oz	2.22%				
TER	WATER	30.9 gl	219.9 gl	196.0 gl	-10.86%			196.0 gl	

ual		Num Batches	1			Manual	14 21 04
id	37897 lb	Design W/C	0.430	Water/Cement	0.430 T	Actual	265.2 gl To Add 43.8 gl
mp	3.00 in #	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water	-2.0 gl / CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/05/2014	BLISS	0137	BRIAN LINDELOF	1093698		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT- SIDEWALK ON SOUTH SIDE OF PARKING LOT				
			NOTE:				
38,097			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
104	TEC# 000003471 8	ROCKCHALKPAR		SIDEWLK	184	4	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	40	40		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	4		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1530	ARRIVE JOB 1549	START UNLOAD 1610	FINISH UNLOAD 1635
LEAVE JOB 1715	ARRIVE PLANT 1735	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 0.40 gal 0.00 yds 0.00 gal 0.00 yds 0.00 gal 0.00

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME

TITLE

X [Signature]
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Waste
CKGMKC	KC APPROVED G	1630 lb	16528 lb	16530 lb	0.01%	1.40% M		27 gl	
NDFAA	PAI LAWRENCE	1332 lb	13662 lb	13700 lb	0.28%	2.57% A		41 gl	
MENT	BUZZI CG	450 lb	4500 lb	4510 lb	0.22%				
%G	HOLCIM IND	150 lb	1500 lb	1500 lb	0.00%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	300.00 oz	0.00%				
11	WR GRACE DAR/	4.50 oz #	45.00 oz	45.00 oz	0.00%				
WATER		30.9 gl	220.7 gl	220.0 gl	-0.32%			220.0 gl	

Design Water/Cement 0.429 T Design 309.0 gl Actual 288.4 gl To Add 20.6 gl

Manual 15 20 44

mp 4.00 in Water in Truck 0.0 gl Adjust Water 0.0 gl / Load Trim Water -2.0 gl / CY



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/05/2014	BLISS	0195	Marty Trumble	1093681		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW) MACHINE CURB				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
54	TEC# 000003471 8	ROCKCHALKPAR		MACHINE	139	1.25	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K .42 25%	50	50		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			
LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	SUBTOTAL			
1:00	1:16	1:48	1:59				
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	BEFORE H2O ADDED	TAX			
1:07	1:23	<input type="checkbox"/> YES <input type="checkbox"/> NO	<input type="checkbox"/> YES <input type="checkbox"/> NO				
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal				TOTAL			
				GRAND TOTAL			

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C38, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature: ASTM C1064, density and/or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey
PRINTED NAME

Super
TITLE

x Sunflower
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wet
CKGMKC	KC APPROVED G	1622 lb	16447 lb	16480 lb	0.20%	1.40% M		27 gl	
NDFAA	PAI LAWRENCE	1327 lb	13585 lb	13700 lb	0.84%	2.38% A		38 gl	
MENT	BUZZI CG	450 lb	4500 lb	4530 lb	0.67%				
AG	HOLCIM IND	150 lb	1500 lb	1555 lb	3.67%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	300.00 oz	0.00%				
1	WR GRACE DAR/	6.00 oz #	60.00 oz	59.00 oz	-1.67%				
TER	WATER	30.2 gl	207.0 gl	206.0 gl	-0.48%			206.0 gl	

Material	Design W/C	Num Batches	Water/Cement	Design	Manual	To Add
id	38007 lb	1	0.414 T	302.0 gl	10.5630	30.6 gl
mp	1.25 in #	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water
					-3.0 gl /	CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	05/06/2014	BLISS	0161	TRAVIS WORRELL	1093727
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW)		
			NOTE:		
30,479			ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
66	TEC# 000003471 8	ROCKCHALKPAR		HANDCURB	139	3

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	38	38		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1528	ARRIVE JOB 1549	START UNLOAD 1551	FINISH UNLOAD 1616
LEAVE JOB 1647	ARRIVE PLANT 1829	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL	
TAX	
TOTAL	

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, nose immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C231 or ASTM C173, Slump: ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

Bliss Sports X
PRINTED NAME TITLE CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	13183 lb	13210 lb	0.20%	1.10% M		17 gl	
NDFAA	PA1 LAWRENCE	1332 lb	10927 lb	10960 lb	0.30%	2.54% A		33 gl	
MENT	BUZZI CG	450 lb	3600 lb	3625 lb	0.69%				
AG	HOLCIM IND	150 lb	1200 lb	1215 lb	+ 1.25%				
REDUCE1	WE GRACE ADV/	30.00 oz	240.00 oz	239.00 oz	-0.42%				
11	WR GRACE DAR/	4.50 oz #	36.00 oz	35.00 oz	-2.78%				
ITER	WATER	30.9 gl	173.5 gl	174.0 gl	0.28%			174.0 gl	

ual	Num Batches	1				Manual	15 24 37				
id	30479 lb	Design W/C	0.430	Water/Cement	0.426 T	Design	247.2 gl	Actual	223.8 gl	To Add	23.4 gl
mp	3.00 in #	Water in Truck	0.0 gl	Adjust Water		0.0 gl / Load	Trim Water	-3.0 gl /	CYL		



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PIKENT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/06/2014	BLISS	0195	Marty Trumble	1093719		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT (SUNFLOWER CREW)				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK		
100	TEC# 000003471	ROCKCHALKPAR		PAVING	113		
	8				4		
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	20	20		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	
1003	1017	1039	1059	
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	BEFORE H2O ADDED	
1109	1135	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal				

SUBTOTAL
TAX
TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways and other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength. Air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143 Temperature, ASTM C1064 density and or yield ASTM C138 Slump and air entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey *Boiss* *Casey*

PRINTED NAME: _____ TITLE: _____ CUSTOMER SIGNATURE: _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	16528 lb	16540 lb	0.07%	1.40% M		27 gl	
NDFAA	PAI LAWRENCE	1332 lb	13680 lb	13750 lb	0.51%	2.70% A		43 gl	
MENT	BUZZI CG	450 lb	4500 lb	4515 lb	0.33%				
AG	HOLCIM IND	150 lb	1500 lb	1505 lb	0.33%				
REDUCE1	WE GRACE ADV/	30 00 oz	300 00 oz	300 00 oz	0.00%				
!!	WR GRACE DAR/	4 50 oz #	45 00 oz	45 00 oz	0.00%				
WATER	WATER	30 9 gl	218 5 gl	218 0 gl	-0.24%			218 0 gl	

Manual	9 58 49	
Actual	288 7 gl	To Add
Design	309 0 gl	20 3 gl
Water/Cement	0 428 T	
Design	309 0 gl	
Water in Truck	0 0 gl	
Adjust Water	0 0 gl / Load	
Trim Water	-2 0 gl /	CYC



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 05/07/2014	ACCOUNT BLISS	TRUCK 0160	DRIVER NAME Joseph Tate	TICKET # 1093750
CUSTOMER NAME BLISS SPORTS LLC JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO BUILDING - EAST ON DIRT BY JOB TRAILER TO CURB CREW		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

38,014

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
76	TEC# 000003471 8	ROCKCHALKPAR		HANDCURB	114	3

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	30	28		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 1405	ARRIVE JOB 1425	START UNLOAD 1425	FINISH UNLOAD 1535
LEAVE JOB 1600	ARRIVE PLANT 1615	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.
PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No compensation accepted after concrete has been batched.
MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Mike
PRINTED NAME

Grenon
TITLE

Mike
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	16447 lb	16450 lb	0.02%	0.90% M		18 gl	
NDFAA	PAI LAWRENCE	1332 lb	13870 lb	13700 lb	0.22%	2.63% A		42 gl	
MENT	BUZZI CG	450 lb	4500 lb	4500 lb	0.00%				
%G	HOLCIM IND	150 lb	1500 lb	1515 lb	1.00%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	300.00 oz	0.00%				
t1	WR GRACE DAR/	4.50 oz #	45.00 oz	45.00 oz	0.00%				
WATER		30.9 gl	219.5 gl	219.0 gl	-0.24%			219.0 gl	

uai	Num Batches	1					Manual	13 59 32
id	38014 lb Design W/C	0.430	Water/Cement	0.429 T	Design	309.0 gl	Actual	278.6 gl To Add 30.4 gl
mp	3.00 in # Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water	-3.0 gl /	CYL	



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
PARTNER OF EXCELLENCE
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	05/08/2014	BLISS	0139	Kevin Tolbert	1093812
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO NORTH PARKING LOT - EASTON SOUTH SIDE OF BUILDING- PAVING ON NORTH SIDE OF REC CENTER		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

19,079

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
12	TEC# 000003471	ROCKCHALKPAR		MAINLINE	137	4

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
5.00	yd	AS6425G4	KCMMB 4K 25% .44	195	195		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT 4:25	ARRIVE JOB 4:40	START UNLOAD 4:45	FINISH UNLOAD 5:05
LEAVE JOB 5:15	ARRIVE PLANT 5:30	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Casey

PRINTED NAME _____ TITLE _____

X CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	8191 lb	8200 lb	0.11%	0.50% M		5 gl	
NDFAA	PAI LAWRENCE	1332 lb	6826 lb	6840 lb	0.18%	2.52% A		20 gl	
MENT	BUZZI CG	450 lb	2250 lb	2275 lb	1.11%				
AG	HOLCIM IND	150 lb	750 lb	760 lb	1.33%				
REDUCE1	WE GRACE ADV/	30.00 oz	150.00 oz	150.00 oz	0.00%				
11	WR GRACE DAR/	4.00 oz	20.00 oz	20.00 oz	0.00%				
ATER	WATER	30.9 gl	119.5 gl	119.0 gl	-0.44%			119.0 gl	

ual	Design W/C	0.430	Water/Cement	0.425	T	Design	154.5 gl	Actual	144.0 gl	To Add	10.5 gl
mp	Water in Truck	0.0 gl	Adjust Water	0.0 gl	/ Load	Trim Water	-2.0 gl	/	CYE		



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications



PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	05/08/2014	BLISS	0192	R L Henley	1093778

CUSTOMER NAME BLISS SPORTS LLC	ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HALL RD NORTH TO BUILDING - EAST ON DIRT BY JOB TRAILER TO CURB CREW
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS	



26,729

NOTE:
ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES,
STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP
29	TEC# 000003471	ROCKCHALKPAR		HANDCURB	206	2
	8					

QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
7.00	yd	AS6425G4	KCMMB 4K 25% .44	30	17		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			
		1 ea Roll Poly		1	1		

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
9:00	9:50	10:00	10:30
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	TEST CYLINDERS TAKEN AFTER H2O ADDED
10:45	11:05	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

SUBTOTAL
TAX
TOTAL

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.

ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173 Slump ASTM C143, Temperature, ASTM C1064 density and or yield ASTM C136 Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

RECEIVED IN GOOD CONDITION BY

PRINTED NAME: _____ TITLE: _____ CUSTOMER SIGNATURE: _____
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	11467 lb	11490 lb	0.20%	0.50% M		7 gl	
NDFAA	PAJ LAWRENCE	1332 lb	9576 lb	9590 lb	1.19%	2.70% A		31 gl	
MENT	BUZZI CG	450 lb	3150 lb	3155 lb	0.16%				
%G	HOLCIM IND	150 lb	1050 lb	1060 lb	0.95%				
REDUCE1	WE GRACE ADV/	30.00 oz	210.00 oz	210.00 oz	0.00%				
!!	WR GRACE DAR/	5.00 oz	35.00 oz	36.00 oz	2.86%				
ATER	WATER	30.9 gl	158.3 gl	158.0 gl	-0.17%			158.0 gl	

Manual	940.39
Actual	195.4 gl
To Add	20.9 gl
CYT	

Num Batches	1
Design W/C	0.430
Water/Cement	0.428
Adjust Water	0.0 gl
Design	216.3 gl
Actual	195.4 gl
To Add	20.9 gl
Trm Water	-3.0 gl



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/09/2014	BLISS	0195	Marty Trumble	1093833		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH TURNS WEST - HAUL RD NORTH NORTH PARKING LOT - HEAD AROUND WEST SIDE OF BUIDLING AND BACK TO THE EAST ON NORTH SIDE				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
78		ROCKCHALKREC		MAINLINE	113	4	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
1.00	yd	AS6425G4	KCMMB 4K 25% .44	101	101		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

SUBTOTAL

TAX

TOTAL

GRAND TOTAL

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO	

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature: ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. **MSDS and Lien Law information on reverse side.**

RECEIVED IN GOOD CONDITION BY

X

CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME

TITLE

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	1643 lb	1660 lb	+	1.03%	0.80% M	2 gl	
NDFAA	PAI LAWRENCE	1332 lb	1370 lb	1390 lb	+	1.47%	2.84% A	5 gl	
MENT	BUZZI CG	450 lb	450 lb	470 lb		4.44%			
AG	HOLCIM IND	150 lb	150 lb	160 lb		6.67%			
REDUCE1	WE GRACE ADV/	30.00 oz	30.00 oz	30.00 oz		0.00%			
!1	WR GRACE DAR/	4.00 oz #	4.00 oz	5.00 oz		25.00%			
TER	WATER	30.9 gl	22.8 gl	24.0 gl	*	5.24%		24.0 gl	

Num Batches: 1
 Design W/C: 0.430 Water/Cement: 0.409 T Design 30.9 gl Actual 30.2 gl To Add: 0.7 gl
 Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYL



PENNY'S

CONCRETE, INC.

23400 W. 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH: (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474

www.pennysconcrete.com
An Equal Opportunity Employer




American Concrete Institute®
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/09/2014	BLISS	0139	Kevin Tolbert	1093861		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAM WAY NORTH TURNS WEST - HAUL RD NORTH NORTH PARKING LOT - HEAD AROUND WEST SIDE OF BUIDLING AND BACK TO THE EAST ON NORTH SIDE				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
79		ROCKCHALKREC		MAINLINE	122	4	
QTY.	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	120	120		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input type="checkbox"/> NO	BEFORE H2O ADDED <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery, if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39; air content: ASTM C231 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	16430 lb	16530 lb	0.61%	0.80% M		16 gl	
NDFAA	PAI LAWRENCE	1332 lb	13655 lb	13670 lb	0.11%	2.51% A		40 gl	
MENT	BUZZI CG	450 lb	4500 lb	4510 lb	0.22%				
AG	HOLCIM IND	150 lb	1500 lb	1505 lb	0.33%				
REDUCE1	WE GRACE ADV/	30.00 oz	300.00 oz	300.00 oz	0.00%				
11	WR GRACE DAR/	4.00 oz #	40.00 oz	40.00 oz	0.00%				
WATER		30.9 gl	233.3 gl	234.0 gl	0.31%			234.0 gl	

Num Batches: 1 Manual 16:15:42

Design 309.0 gl Actual 289.9 gl To Add: 19.1 gl

mp: 4.00 in Water in Truck: 0.0 gl Adjust Water: 0.0 gl / Load Trim Water: -2.0 gl / CYE



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PIANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	05/14/2014	BLISS	0137	BRIAN LINDELOF	1093915
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAM WAY NORTH TURNS WEST - HAUL RD NORTH TO JOB (BRUCE W/ LITHKO) ISOLATIONS		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		

30,551

ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
53		ROCKCHALKREC		PAVING	139	4	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
8.00	yd	AS6425G4	KCMMB 4K 25% .44	168	168		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			

SUBTOTAL
TAX
TOTAL
GRAND TOTAL

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
1619	1633	1656	1715
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	BEFORE H2O ADDED
1729	1745	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, nose immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and/or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064 density and/or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

_____ X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

lenal	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	13118 lb	13150 lb	0.24%	0.60% M		9 gl	
NDFAA	PAI LAWRENCE	1332 lb	10966 lb	11000 lb	0.31%	2.91% A		37 gl	
MENT	BUZZI CG	450 lb	3600 lb	3630 lb	0.83%				
AG	HOLCIM IND	150 lb	1200 lb	1210 lb	0.83%				
REDUCE1	WE GRACE ADV/	30.00 oz	240.00 oz	240.00 oz	0.00%				
tt	WR GRACE DAR/	4.50 oz	35.00 oz	37.00 oz	2.78%				
TER	WATER	30.9 gl	164.6 gl	185.0 gl	0.20%			185.0 gl	

ual	Num Batches	1	Manual	16.13.43								
id	30551 lb	Design W/C	0.430	Water/Cement	0.426	T	Design	247.2 gl	Actual	231.7 gl	To Add	15.5 gl
mp	4.00 in	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trim Water	-2.0 gl / CYL					



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
STATEMENT OF REGISTRATION
Certifications

www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 05/15/2014	ACCOUNT BLISS	TRUCK 0206	DRIVER NAME Wayne Grammer	TICKET # 1093950				
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - CREW POURING BY THE TICKET BOOTH AT BASE OF RAMP TO STADIUM						
JOB ADDRESS 6100 ROCK CHALK DR - ROCK CHALK PARK - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!						
3,854									
ORDER # 104	PO# TEC# 000003471 8	PROJECT CODE ROCKCHALKPAR	JOB#	APPLICATION MAINLINE	PREVIOUS TRUCK 184	SLUMP 5			
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT		
1.00	yd	AS6425G4	KCMMB 4K 25% .44	21	21				
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0					
LEAVE PLANT 12:37				ARRIVE JOB 12:45		START UNLOAD 1:04		FINISH UNLOAD 1:25	
LEAVE JOB 1:36				ARRIVE PLANT 1:41		TEST CYLINDERS TAKEN <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		SUBTOTAL	
						BEFORE H2O ADDED <input type="checkbox"/> YES <input checked="" type="checkbox"/> NO		TAX	
PURCHASER OF THIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal								TOTAL	
CAUTION! Cement powder or freshly mixed concrete grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side.								GRAND TOTAL	
ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK									
DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.									
PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.									
ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.									

RECEIVED IN GOOD CONDITION BY

Bliss
PRINTED NAME

TITLE

Bliss
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

enal	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	1641 lb	1650 lb	0.52%	0.70% M		1 gl	
NDFAA	PAI LAWRENCE	1332 lb	1366 lb	1410 lb	+ 3.23%	2.54% A		4 gl	
MENT	BUZZI CG	450 lb	450 lb	450 lb	0.00%				
AG	HOLCIM IND	150 lb	150 lb	150 lb	0.00%				
REDUCE1	WE GRACE ADV/	30.00 oz	30.00 oz	30.00 oz	0.00%				
11	WR GRACE DAR/	4.50 oz #	4.50 oz	4.00 oz	-11.11%				
ATER	WATER	30.9 gl	23.5 gl	23.0 gl	-2.03%			23.0 gl	

ual	Num Batches	1	Manual	12 32 42
id	3854 lb	Design W/C 0.430	Water/Cement 0.430 T	Design 30.9 gl
mp	5.00 in #	Water in Truck 0.0 gl	Adjust Water 0.0 gl / Load	Trim Water -2.0 gl / CYL
			Actual 28.6 gl	To Add 2.3 gl



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
Manufacturer of Inspection
Certifications

PLANT #	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #		
01	05/21/2014	BLISS	0206	Wayne Grammer	1094068		
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH TO JOB				
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS							
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK	SLUMP	
109		ROCKCHALKREC		SIDEWLK	122	4	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
10.00	yd	AS6425G4	KCMMB 4K 25% .44	50	50		
10.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	5		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			
SUBTOTAL							
TAX							
TOTAL							
GRAND TOTAL							

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
11:21	11:38	12:11	11:00
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
11:21	11:38	BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal			

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138. Slump and air entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Bliss
PRINTED NAME _____ TITLE _____
x Bliss
CUSTOMER SIGNATURE _____
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Water
CKGMKC	KC APPROVED G	1630 lb	16414 lb	16440 lb	0.16%	0.70% M		14 gl	
NDFAA	PAI LAWRENCE	1332 lb	13640 lb	13670 lb	0.22%	2.40% M		38 gl	
MENT	BUZZI CG	450 lb	4500 lb	4510 lb	0.22%				
%G	HOLCIM IND	150 lb	1500 lb	1515 lb	1.00%				
REDUCE	WE GRACE ADV/	30.00 oz	300.00 oz	301.00 oz	0.33%				
TER	WR GRACE DAR/	4.80 oz #	48.00 oz	48.00 oz	0.00%				
TER	WATER	30.9 gl	237.0 gl	237.0 gl	-0.01%			237.0 gl	

Material	Design	Water/Cement	Adjust Water	Design	Actual	To Add
Manual	12 40 30					
yd	38135 lb	0.430	0.428 T	309.0 gl	289.1 gl	19.9 gl
mp	4.00 in	Water in Truck	0.0 gl	0.0 gl / Load	-2.0 gl /	CYT



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
Department of Transportation
Certifications

PLANT	DATE	ACCOUNT	TRUCK	DRIVER NAME	TICKET #
01	05/21/2014	BLISS	0137	BRIAN LINDELOF	1094072
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS		
JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS			6TH ST. WEST - GEORGE WILLIAM WAY NORTH TURNS WEST - HAUL RD NORTH TO JOB (HAND CURB - BLISS CREW)		
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATION	PREVIOUS TRUCK
150		ROCKCHALKREC		HANDCURB	
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED
2.50	yd	AS6425G4	KCMMB 4K 25% .44	2.5	2.5
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0	
					SLUMP
					3

SUBTOTAL

TAX

TOTAL

GRAND TOTAL

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
1507	1530	1522	1541
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN	<input type="checkbox"/> YES
1610	1631	BEFORE H2O ADDED	<input type="checkbox"/> YES

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds 3 gal 7 yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, and other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

X 
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME TITLE

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
KCKMKC	KC APPROVED G	1630 lb	4104 lb	4120 lb		0.40%		3 gl	
NDFAA	PAI LAWRENCE	1332 lb	3410 lb	3470 lb	+	1.76%		10 gl	
MENT	BUZZI CG	450 lb	1125 lb	1135 lb		0.89%			
%G	HOLCIM IND	150 lb	375 lb	390 lb	+	4.00%			
REDUCE1	WE GRACE ADV/	30 00 oz	75 00 oz	75 00 oz		0.00%			
11	WR GRACE DAR/	4 80 oz #	12 00 oz	13 00 oz		8.33%			
ATER	WATER	30 9 gl	56 8 gl	55 0 gl	-	3.09%		55 0 gl	

ual	Num Batches	1	Manual	15 02 18
id	9579 lb Design W/C	0.430	Water/Cement	0.423 T
mp	3 00 in # Water in Truck	0 0 gl	Adjust Water	0 0 gl / Load
			Design	77 3 gl
			Actual	68 2 gl
			To Add	9 1 gl
			Manual	15 02 18
			Actual	68 2 gl
			To Add	9 1 gl
			Manual	15 02 18
			Actual	68 2 gl
			To Add	9 1 gl



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474



American Concrete Institute
Certifications



Certifications

KANSAS
DEPARTMENT OF TRANSPORTATION
Certifications

PLANT 01	DATE 05/22/2014	ACCOUNT BLISS	TRUCK 0206	DRIVER NAME Wayne Grammer	TICKET # 1094087
CUSTOMER NAME BLISS SPORTS LLC JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH TURNS WEST - HAUL RD NORTH TO JOB (SIDEWALK RAMP)		
11,429			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
ORDER # 105	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION SIDEWLK	PREVIOUS TRUCK 114
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED
3.00	yd	AS6425G4	KCMMB 4K 25% .44	11	11
3.00	/y	FIBERS	GRACE POLYPROPYLENE FI	1	2
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0	
					SLUMP 4

SUBTOTAL

TAX

TOTAL

GRAND TOTAL

LEAVE PLANT 10:32	ARRIVE JOB 10:30	START UNLOAD 10:38	FINISH UNLOAD 11:00
LEAVE JOB 11:32	ARRIVE PLANT 11:30	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mortar gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing. Towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Bliss
PRINTED NAME

TITLE

x Bliss
CUSTOMER SIGNATURE

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Serial	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMKC	KC APPROVED G	1630 lb	4924 lb	4930 lb	0.12%	0.70% M		4	gl
NDFAA	PAI LAWRENCE	1332 lb	4108 lb	4120 lb	0.29%	2.80% M		13	gl
MENT	BUZZI CG	450 lb	1350 lb	1355 lb	0.37%				
AG	HOLCIM IND	150 lb	450 lb	450 lb	0.00%				
REDUCE1	WE GRACE ADV/	30.00 oz	90.00 oz	91.00 oz	1.11%				
11	WR GRACE DAR/	4.70 oz #	14.10 oz	14.00 oz	-0.71%				
ATER	WATER	30.9 gl	69.2 gl	68.0 gl	-1.72%			68.0	gl

ual	Design	Num Batches	1	Manual	10 13 41
id	11429 lb	Design W/C	0.430	Actual	85.6 gl
mp	4.00 in	Water in Truck	0.0 gl	To Add	7.1 gl
		Adjust Water	0.0 gl		
		Design	92.7 gl		
		Trim Water	-2.0 gl		



PENNY'S

CONCRETE, INC.

23400 W 82ND STREET

SHAWNEE MISSION, KANSAS 66227-2705

DISPATCH (913) 441-4197 OFFICE (913) 441-8781

(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications



www.pennysconcrete.com
An Equal Opportunity Employer

PLANT 01	DATE 05/23/2014	ACCOUNT BLISS	TRUCK 0117	DRIVER NAME BRIAN LINDELOF	TICKET # 1094131		
CUSTOMER NAME BLISS SPORTS LLC JOB ADDRESS ROCK CHALK PARK - REC. & WELNESS CENTER - LAWRENCE, KS			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH WEST - GEORGE WILLIAMS WAY NORTH TURNS WEST - HAUL RD NORTH- HEAD EAST ON DIRT SOUTH OF REC CENTER TO EAST SIDE OF REC CENTER (SIDEWALK)				
			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!				
ORDER # 123	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION	PREVIOUS TRUCK 122		
SLUMP 4							
QTY	UNIT	PRODUCT	DESCRIPTION	ORDERED	DELIVERED	UNIT PRICE	AMOUNT
7.00	yd	AS6425G4	KCMMB 4K 25% .44	77	77		
7.00	/y	FIBERS	GRACE POLYPROPYLENE FI	77	77		
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0			
SUBTOTAL							
TAX							
TOTAL							
GRAND TOTAL							

LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input type="checkbox"/> NO <input type="checkbox"/> YES <input type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS yds gal yds gal yds gal yds gal

CAUTION: Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways, all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173 Slump ASTM C143 Temperature, ASTM C1064, density and or yield ASTM C138 Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Lien Law information on reverse side.

RECEIVED IN GOOD CONDITION BY _____

X
CUSTOMER SIGNATURE
NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

PRINTED NAME _____ TITLE _____

Item	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Wat
CKGMC	KC APPROVED G	1630 lb	11490 lb	11510 lb	0.18%	0.70% M		10 gl	
NDFAA	PAI LAWRENCE	1332 lb	9564 lb	9540 lb	0.80%	2.57% A		29 gl	
MENT	BUZZI CG	450 lb	3150 lb	3150 lb	0.00%				
AG	HOLCIM IND	150 lb	1050 lb	1065 lb	+ 1.43%				
REDUCE1	WE GRACE ADV	30.00 oz	210.00 oz	210.00 oz	0.00%				
t1	WR GRACE DAR	4.80 oz #	33.60 oz	33.00 oz	-1.79%				
TER	WATER	30.9 gl	164.0 gl	164.0 gl	-0.01%			164.0 gl	

Num Batches	1		Manual	16.30.55
id	26749 lb	Design W/C 0.430	Water/Cement 0.428 T	Design 216.3 gl
mp	4.00 in	Water in Truck 0.0 gl	Adjust Water 0.0 gl / Load	Actual 202.5 gl To Add 13.8 gl
			Tnm Water	-2.0 gl / CYL



www.pennysconcrete.com
An Equal Opportunity Employer

PENNY'S

CONCRETE, INC.

23400 W 82ND STREET
SHAWNEE MISSION, KANSAS 66227-2705
DISPATCH (913) 441-4197 OFFICE (913) 441-8781
(800) 322-9710 (800) 524-6474




American Concrete Institute
Certifications



Certifications

KANSAS
A PART OF THE REGISTRATION
Certifications

PLANT 01	DATE 05/27/2014	ACCOUNT BLISS	TRUCK 0112	DRIVER NAME TONY RICHESON	TICKET # 1094157
CUSTOMER NAME BLISS SPORTS LLC			ADDITIONAL DIRECTIONS AND/OR SPECIAL INSTRUCTIONS 6TH ST. WEST - GEORGE WILLIAM WAY NORTH TURNS WEST - HAUL RD NORTH TO END - EAST TO PUMP		
JOB ADDRESS ROCK CHALK PARK 1/2 REC. & WELNESS CENTER - LAWRENCE, KS			NOTE: ALL DRIVERS MUST WEAR A HARD HAT, SAFETY GLASSES, STEEL TOE BOOTS, AND SAFETY VEST ON EVERY JOB!		
			22,790		
ORDER # 103	PO#	PROJECT CODE ROCKCHALKREC	JOB#	APPLICATION HANDCURB	PREVIOUS TRUCK 3
QTY 6.00	UNIT yd	PRODUCT AS6425G4	DESCRIPTION KCMMB 4K 25% .44	ORDERED 6	DELIVERED 6
1.00	ea	FUELINV	FUEL SURCHARGE - PER I	0	
SUBTOTAL					
TAX					
TOTAL					
GRAND TOTAL					

LEAVE PLANT 4:13	ARRIVE JOB 4:31	START UNLOAD 4:38	FINISH UNLOAD 5:24
LEAVE JOB 5:27	ARRIVE PLANT 5:57	TEST CYLINDERS TAKEN BEFORE H2O ADDED	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

PURCHASER OR HIS AUTHORIZED REPRESENTATIVE ACCEPTS RECEIPT OF THIS LOAD OF MATERIAL AND HAS INSTRUCTED THE DRIVER TO ADD WATER AS FOLLOWS: yds gal yds gal yds gal yds gal

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse immediately and repeatedly with water and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK.

DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery if ground conditions beyond the curb line are inadequate for heavy truck travel and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength ASTM C31 & ASTM C39, air content ASTM C231 or ASTM C173, Slump ASTM C143, Temperature, ASTM C1064, density and or yield ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing and protection of all concrete after delivery to the curb line. The placement, consolidation, curing and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer.

ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched. MSDS and Len Law information on reverse side.

RECEIVED IN GOOD CONDITION BY

Bliss x Bliss

PRINTED NAME: _____ TITLE: _____ CUSTOMER SIGNATURE: _____

NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Material	Description	Design Qty	Required	Batched	% Var	% Moisture	% AbsP	Actual	Water
CKGMKC	KC APPROVED G	1630 lb	9848 lb	9850 lb	0.02%	0.70% M		8	gl
NDFAA	PAI LAWRENCE	1332 lb	8240 lb	8240 lb	0.00%	3.10% M		30	gl
MENT	BUZZI CG	450 lb	2700 lb	2710 lb	0.37%				
AG	HOLCIM IND	150 lb	900 lb	900 lb	0.00%				
REDUCE1	WE GRACE ADV	30.00 oz	180.00 oz	180.00 oz	0.00%				
W	WR GRACE DAR	4.80 oz #	28.80 oz	29.00 oz	0.69%				
WATER		30.9 gl	129.5 gl	129.0 gl	-0.39%			129.0	gl

Material	Design W/C	0.430	Water/Cement	0.429 T	Design	185.4 gl	Actual	166.9 gl	To Add	18.5 gl
Material	Water in Truck	0.0 gl	Adjust Water	0.0 gl / Load	Trm Water	-3.0 gl /	CYC			